



# AV/PAL-TWIN-Modulator

Convert 2 AV signals into 2 analogue PAL B/G channels

EAN	Item no.	Weight (Box)	Weight	Box
4019588059863	0000/5986	300 g	300 g	8,5 x 16,5 x 47,5 cm

## AMBIENT OPERATING CONDITIONS

Ambient temperature: 0 ... 45 °C

Humidity: 10 ... 90 %

## CONNECTIONS

Ethernet 10/100 (RJ-45): Yes Remote-Control

Video IN: 1

Audio input analogue (RCA): Yes

## GENERAL CHARACTERISTICS

Top features: 2x Analogue AV input, PAL/NTSC, SECAM

Top features: Stereo sound

Top features: Two adjacent analog channels output in range of 48...860 MHz

Top features: Output level 100 dBµV per channel

Top features: Control and supervision by web interface or external handset

## RF MODULATOR

Modulation: CCIR PAL B/G

## RF OUTPUT CONVERTER

Harmonic product:  $\leq -50$  dB typisch

Noise:  $\leq 45$  typisch

C/N:  $\geq 45$  dB typisch

Output frequency: 48 ... 860 MHz

Output level: 100 dB per channel

## SCOPE OF DELIVERY

AV/PAL TWIN Modulator, Frontblende, Rückblende, AV-Adapterkabel