



SCR-LNB

SCR-LNB with 2 legacy outputs

EAN	Colour	Item no.	Weight (Box)	Weight	Device (W x H x D)	Box
4019588178861	beige	0017/8886	344 g	292 g	14,5 x 6 x 11,5 cm	12,3 x 6,5 x 15 cm

TOP FEATURES

4 Receiver mit SCR-Unterstützung anschließbar

2 Receiver über Legacy-Ausgang anschließbar

SCR-Protokoll gemäß EN 50494

Wetterschutzgehäuse

Feed-ø 40 mm

SONSTIGES

bf_filter_number_of_participants: 6

bf_filter_number_satellites: 1

LOCAL OSCILLATOR

Low band: 9,75 GHz

High band: 10,6 GHz

Accuracy: ± 1 MHz

Temperature drift: ± 3 MHz

Phase noise: -80 @10kHz

LNB CONTROL

Vertical: 11,5 ... 14 V

Horizontal: 16 ... 19 V

Band switch: 22 kHz

DiSEqC: 1

AMBIENT OPERATING CONDITIONS

Ambient temperature: -30 ... 60 °C

GENERAL CHARACTERISTICS

Colour: white

INPUT FREQUENCY RANGE

Low band: 10,7 ... 11,7 GHz

High band: 11,7 ... 12,75 GHz

NOISE FACTOR

Noise figure: 1 dB

OUTPUT FREQUENCY RANGE

Low band: 950 ... 1.950 MHz

High band: 1.100 ... 2.150 MHz

POWER SUPPLY

Power consumption: max. 280 mA @13,5 V

SINGLE-CABLE OUTPUT

Output frequency: 950 ... 2.150 MHz

Number of output channels: 4

Frequency of the output channels: 1210, 1420,
1680, 2040 MHz

TECHNICAL DATA

Outputs: 3 ; 1x SCR (gilded), 2x Legacy

Amplification: 57 dB

Feed reception: ø 40 mm

Connector type: F-Buchse

Impedance: 75 Ω

SCOPE OF DELIVERY

TechniSat SCR-LNB