



TECHNISWITCH 5/8

Multi-switch system with connection possibility of 4 levels for distribution to up to 16 participants

EAN	Colour	Item no.	Weight (Box)	Weight
4019588132597	blue/yellow	0001/3259	776 g	776 g
4019588032590	blue/yellow	0000/3259	350 g	350 g
4019588232594	blue/yellow	3222/3259	400 g	300 g

AMBIENT OPERATING CONDITIONS

Ambient temperature: -25 ... 55 °C

AMPLIFICATION

Sat: -2 ... 3 dB

Terrestrial: -4 ... -1 dB

DECOUPLING

Output: > 35 dB

GENERAL CHARACTERISTICS

Top Features: Ohne Dämpfung im Sat-Bereich

Top Features: Mit Schräglagenentzerrung

Top Features: Für Quattro-LNB

Top Features: Stromsparend ohne Netzteil einsetzbar

POWER SUPPLY

Mains adapter: extern DC 15V/1,2A

Nominal voltage: 100 ... 250 V

Frequency: 50 ... 60 Hz

RECEPTION RANGE

Sat: 950 ... 2.150 MHz

Terrestrial: 47 ... 862 MHz

TECHNICAL DATA

Satellite inputs: 4

Terrestrial input: 1

Outputs: 8

Distribution length: max. 100 m

SCOPE OF DELIVERY

TechniSwitch 5/8 G2, Power supply, manual