

COAXSAT 140-4.6

High-end quadruple screened RG6 coaxial cable with 140 dB screening

EAN	Cable length	Colour	Item no.	Weight (Box)	Weight	Device (W x H x D)	Box	Coil length
4019588523067		white	0052/3106	29,07 kg	28,43 kg	40 x 40 x 32 cm	55 x 45 x 40 cm	
4019588231061	100 m	white	0002/3106	6,5 kg	6,13 kg	27,5 x 27,5 x 14,5 cm	27,5 x 27,5 x 14,5 cm	100 m
4019588231061	100 m	white	0002/3106	6,5 kg	6,13 kg	27,5 x 27,5 x 14,5 cm	27,5 x 27,5 x 14,5 cm	100 m

TOP FEATURES

Innenleiter aus massivem, hochreinen Elektrolytkupfer!

Physikalisch geschäumtes, stabiles PE-Dieelektrikum = sehr gute Dämpfung und Alterungsbeständigkeit!

Alufolie geklebt, dadurch erleichterte Steckermontage

Geflecht aus verzinntem Kupfer; große optischen Bedeckung. Sehr gute Leitfähigkeit.

Erfüllt EN 50117/ Schirmungsklasse A+

RETURN LOSS
5 - 30 MHz: ≥ 28 dB
30 - 65 MHz: ≥ 28 dB
65 - 470 MHz: ≥ 28 dB
470 - 1800 MHz: ≥ 27 dB
1800 - 2450MHz: ≥ 20 dB

ATTENUATION
5 MHz: 0,48
10 MHz: 2,2
25 MHz: 3
45 MHz: 4
100 MHz: 6,1
200 MHz: 8,7
300 MHz: 9,6
450 MHz: 13,7
800 MHz: 18,5
1000 MHz: 20,5
1350 MHz: 23,5
1750 MHz: 25,6
2050 MHz: 29,4
2250 MHz: 30,5

TECHNICAL DATA
Frequency range: 5 ... 3.000 MHz
Impedance: 75 Ω (± 3)
Inner cable diameter: 1 mm (18AWG)
Inner cable material: Copper bare (OFC)
Isolation: Zell-PE
Diameter dielectric: 4,65 mm (± 0,1)
Outer cable: 1x Alum. foil + 1x tinned coppper braiding + 1x Alum. foil
Sheath: PVC, withe
Diameter with coating: 7 mm (± 0,2)
Bending radius: ≥ 50 mm
Capacity: 55 pF
Shrinkage factor: 0,85
Shielding factor: ≥ 140 dB Klasse A+

TRANSFER IMPEDANCE
5MHz: ≤ 0,7
30 MHz: ≤ 0,15

SCOPE OF DELIVERY
100m reel