



# TECHNISTAR S5

HDTV-Sat-Receiver mit USB-Aufnahmefunktion

Colour	EAN	Item no.	Weight (Box)	Weight	Device (W x H x D)	Box
black	4019588047181	0000/4718	1,23 kg	588 g	22 x 4 x 17,7 cm	31 x 7,8 x 19,5 cm

## TOP FEATURES

HDTV tuner (DVB-S/S2)

DVRready: Digital video recorder function for recording to USB hard drive

Timeshift in connection with USB hard drive

Operation on 12V

Multimedia streaming on home network (via UPnP, server)

Electronic program guide (EPG)

## MULTIMEDIA

DVR function: Ja

DVR storage medium: via USB

Timeshift: Yes

Recordings edition function: Yes

Recordings folder management: Yes

## AMBIENT OPERATING CONDITIONS

Ambient temperature: 5 ... 35 °C

Humidity: 10 ... 75 %

## LNB CONTROL

Vertical: 14 V

Horizontal: 18 V

Band switch: 22 kHz

Current consumption: max. 400 mA (kurzschlussfest)

DiSEqC: 1.0 / 1.2 / SCR1 / SCR2

## TECHNISAT ADDED VALUE SERVICES

ISI-Mode: Yes

ISIPRO: Yes

AUTOINSTALL: Yes

TECHNIFAMILY: Yes

SFI: Yes

## INTERNET/NETWORK

Internet speed test: Yes

## AUDIO

Clear language from ARD: Yes über DVB

## CONNECTIONS

HDMI™ (out): 1

USB: 1 (USB 2.0)

Common Interface Plus (CI+): Yes

Smartcard reader: Yes

Digital electric audio output (S/PDIF): Yes

audio/video output analog (3.5 mm jack): Yes

TechniSat specific adapter set necessary (available at 0000/3649)

Scart: 1 TechniSat-spezifisches Adapterset erforderlich (erhältlich unter 0000/3649)

Ethernet 10/100 (RJ-45): Yes

F socket: 1

DC IN: 1

## DISPLAY

Freeze frame: Yes

SD: Yes

HD: Yes

1080p: Yes

1080i: Yes

720p: Yes

576p: Yes

576i: Yes

Type: 7 segment, 4 digits, white

## NETWORK & COMMUNICATION

Bluetooth: Yes (Audioausgabe, optional via USB-Bluetooth-Adapter Art.-Nr. 0000/3635)

## POWER SUPPLY

Nominal voltage: 230 V

Frequency: 50 Hz

Mains adapter: external DC 12 V / 2 A

## DECODER

Video decoder: MPEG-2 MP@HL/ML, H.264/MPEG-4 AVC

Audio decoder: MPEG-1 & MPEG-2 Layer I, II, III

## HANDLING/COMFORT

Page memory: 1.000

Teletext subtitles: Yes

Media Player: Yes

Ideal for camping: Yes

Selection regional channels: Yes

Clock: Yes

Autostandby: Yes

Teletext: Yes

Sleep timer: Yes

Channel presets: 9.999

Alarm: Yes

## OTHER FEATURES

OSD languages: German, Danish, English, French, Greek, Italian, Dutch, Norwegian, Polish, Portuguese, Russian, Swedish, Spanish, Czech, Turkish, Hungarian

## STREAMING

Cloud store: Ja

DLNA Client: Yes

## DECRYPTION SYSTEM

Conax: Yes

CI+: Yes (v1.3)

## HOTEL MODE

Protected access to hotel mode: Yes

Customisable start screen: Yes

Lockable volume: Yes

Menu locking: Yes

Control panel lock: Yes

Integrated LED clock: Yes

Selectable start source: Yes

Selectable start channel: Yes

## POWER CONSUMPTION

In operation: 4,8 W without LNB

Standby: < 0,3 W

## SUPPORTED FORMATS & CODECS

Video-Codecs: MPEG-2, MPEG-4, H.264

Video-Formats: M4V, MP4, MKV, MOV, MPG, TS, TS4, Xvid, M2TS, AVI, ASF

Picture-Formats: BMP, JPEG, GIF, PNG, TIFF

Audio-Formats: WAV, MP3, AAC, FLAC, MP2, OGG, DDAC3, AIFF

#### TECHNISAT CONNECT

SFI: Yes

#### TUNER

Tuner type: Single-Tuner

DVB-S tuner: 1

Single Cable Solution (SatCR): SCR1 = EN50494,  
SCR2 = EN50607

Satellite radio: Yes

Internet radio: Yes

Reception on: HD-TV, SD-TV

TECHNIROUTER ready: Yes

#### TUNER - SAT

Reception range: 950 ... 2.150 MHz

Viterbi rates: 1/2, 2/3, 3/4, 5/6, 7/8 , (autom.  
Anpassung)

DVB-S: QPSK

DVB-S: 2 ... 45

DVB-S2: 8PSK - QPSK

DVB-S2: 2 ... 45

FEC: Viterbi and Reed-Solomon

#### SCOPE OF DELIVERY

TECHNISTAR S5, remote control with batteries, external mains adapter, HDMI cable, manual