



TECHNINET BS6

Digital 16-way Head-end - DVB-S(2) / DVB-C

Colour	EAN	Item no.	Weight (Box)	Weight	Device (W x H x D)	Box
silver/blue	4019588059931	0000/5993	3,11 kg	2,81 kg	37,5 x 7 x 13,5 cm	44 x 9 x 15,5 cm

TOP FEATURES

Stand-alone head-end with 16-way DVB S(2) frontend and 16 output channels conforming to DVB-C (flexibly configurable)

Power supply for LNB

Comprehensive baseband signal processing with channel filter functionality such as NIT, LCN

Cascade capability for two head-ends - 32 DVB-C output channels

Outstanding output values due to direct implementation as FPGA solution

All transmission parameters can be set using web interface

High level of energy efficiency - only 1,81 Watt per channel

4 Sat-IF inputs with DiSEqC 1.0 functionality for sat multiswitches and 2 additional sat-IF inputs

Remote maintenance and configuration via web interface

No fan, therefore no noise and no maintenance

TUNER (DVB-S2)

DVB-S2 demodulator: EN 302 307

Demodulation: 8PSK, QPSK

Symbol rates: 2 ... 45

Roll off factor: 0,35

FEC block size: 64 kB

FEC Code rate (LDPC): 1/2, 3/5, 2/3, 3/4, 4/5, 5/6, 8/9, 9/10

Outer coding (BCH): GF(2¹⁶), t=8, 10, 12

LNB CONTROL

Vertical: 13 V

Horizontal: 18 V

Band switch: 22 kHz

Current consumption: max. 750 mA total

DiSEqC: 1 (sat. pos. (A/B/C/D))

AMBIENT OPERATING CONDITIONS

Ambient temperature: -10 ... 50 °C

Humidity: 10 ... 75 %

CONFIGURATION, MONITORING

Network interface: RJ45, Ethernet, 100BaseT, TCP/IP

DVB-C OUTPUT

Modulation: 16-, 32-, 64-, 128-, 256-QAM

Symbol rate: 3,5 ... 7,2

MER: Typ. 45 dB (256-QAM, with equaliser)

Reception range: 45 ... 862 MHz

Output level: 90 per carrier, adjustable

Secondary wave suppression: > 50 dB

Signal output: F socket

Output impedance: 75 Ω

Return loss: \geq 14 dB

POWER CONSUMPTION

In operation: 44 W

POWER SUPPLY

Nominal voltage: 230 V

Frequency: 50 Hz

Mains adapter: internal

SAT IF INPUT / MULTISWITCH

Reception range: 950 ... 2.150 MHz

input / output: F-socket

Impedance: 75 Ω

Input level: 45 ... 85

LNB voltage supply: 13 / 18 V & 22kHz

LNB power supply: Max. 250 mA

TUNER DVB-S

DVB-S tuner: 16 Stück

DVB-S demodulator: EN 300 421

Demodulation: QPSK

Symbol rates: 2 ... 45

Roll off factor: 0,35

FEC code rate: 1/2, 2/4, 3/4, 5/6, 6/7, 7/8

Interleaving: Convolutional; l=12

Outer coding: Reed Solomon 204, 188, T=8

SCOPE OF DELIVERY

TECHNINET BS6, Instruction manual