



Line Amplifier 4Z-WB

4-way line amplifier

| EAN | Colour | Item no. | Weight (Box) | Weight | Device (W x H x D) | Box |
|---------------|---------------|-----------|--------------|--------|--------------------|------------------|
| 4019588032446 | silver/yellow | 0000/3244 | 680 g | 450 g | 15 x 10,5 x 3,7 cm | 24 x 12,5 x 5 cm |

AMBIENT OPERATING CONDITIONS

Humidity: 10 - 75 %

Ambient temperature: -25 bis 55 °C

GENERAL CHARACTERISTICS

Top Features: Compensates the attenuation of 80 meters of RG6 cable

Top Features: Frequenzbereich: 250 - 2400 MHz

Top Features: Verstärkung einstellbar (max. 30 dB bei 2400 MHz)

Top Features: Schräglage einstellbar 0 - 8 dB

Top features: Für 2 Wideband-LNBs oder 1 Quattro-LNB

TECHNICAL DATA

Satellite inputs: 4

Distribution length: 80 m

AMPLIFICATION

Sat: 18 - 30 dB

POWER SUPPLY

Nominal voltage: 230 V DC

Frequency: 50 Hz

Mains adapter: external (DC 12 V / 2,0 A)

Power consumption: typ. 560 mA @12V

DECOUPLING

Trunks: 40 dB

RECEPTION RANGE

Sat: 250 - 2.400 MHz

SCOPE OF DELIVERY

Line Amplifier 4Z-WB, power supply, instruction manual