



Line Amplifier 4Z-WB

4-way line amplifier

Colour	EAN	Item no.	Weight (Box)	Weight	Device (W x H x D)	Box
silver/yellow	4019588032446	0000/3244	680 g	450 g	15 x 10,5 x 3,7 cm	24 x 12,5 x 5 cm

<p>AMBIENT OPERATING CONDITIONS</p> <p>Humidity: 10 - 75 %</p> <p>Ambient temperature: -25 bis 55 °C</p>	<p>AMPLIFICATION</p> <p>Sat: 18 - 30 dB</p>	<p>DECOUPLING</p> <p>Trunks: 40 dB</p>
<p>GENERAL CHARACTERISTICS</p> <p>Top Features: Compensates the attenuation of 80 meters of RG6 cable</p> <p>Top Features: Frequenzbereich: 250 - 2400 MHz</p> <p>Top Features: Verstärkung einstellbar (max. 30 dB bei 2400 MHz)</p> <p>Top Features: Schräglage einstellbar 0 - 8 dB</p> <p>Top features: Für 2 Wideband-LNBs oder 1 Quattro-LNB</p>	<p>POWER SUPPLY</p> <p>Nominal voltage: 230 V DC</p> <p>Frequency: 50 Hz</p> <p>Mains adapter: external (DC 12 V / 2,0 A)</p> <p>Power consumption: typ. 560 mA @12V</p>	<p>RECEPTION RANGE</p> <p>Sat: 250 - 2.400 MHz</p>
<p>TECHNICAL DATA</p> <p>Satellite inputs: 4</p> <p>Distribution length: 80 m</p>	<p>SCOPE OF DELIVERY</p> <p>Line Amplifier 4Z-WB, power supply, instruction manual</p>	