



EUTELASTRASAT 850, 2 participant

With the TechniSat EUTELASTRASAT appliance you receive the TV and radio programmes of ASTRA 19.2° East and EUTELSAT 13° East

EAN	Colour	Item no.	Weight (Box)	Weight	Device (W x H x D)	Box
4019588742826	brick/red	9742/8882	9,6 kg	6 kg	85 x 87 cm	88 x 95 x 24 cm
4019588752825	yellow with Smiley	9752/8882	9,6 kg	6 kg	85 x 87 cm	88 x 95 x 24 cm
4019588297081	beige	9702/8882	9,6 kg	6 kg	85 x 87 cm	88 x 95 x 24 cm
4019588732827	slate/grey	9732/8882	9,6 kg	6 kg	85 x 87 cm	88 x 95 x 24 cm
4019588772823	polar white	9772/8882	9,6 kg	6 kg		
4019588722828	fir/green	9722/8882			85 x 87 cm	88 x 95 x 24 cm

LOCAL OSCILLATOR

Low band: 9,75 GHz $\pm$ 3MHz

High band: 10,6 GHz $\pm$ 3MHz

LNB CONTROL

Vertical: 11,5 - 14,5 V

Horizontal: 16 - 19 V

GENERAL CHARACTERISTICS

Top features: Für 2 Teilnehmer

Material: Aluminium

Top features: 2 Orbitpositionen (Astra 19,2° Ost und Eutelsat Hotbird 13° Ost)

Top features: Optimal für Dachmontage

Material strength: 1,6 mm

Coating: Powder-coated on both sites

INPUT FREQUENCY RANGE

Low band: 10,7 - 11,7 GHz

High band: 11,7 - 12,75 GHz

NOISE FACTOR

Lower frequency range: 0,6 dB max.

Upper frequency range: 0,6 dB max.

OUTPUT FREQUENCY RANGE

Low band: 950 - 1.950 MHz

High band: 1.100 - 2.150 MHz

TECHNICAL DATA

F/D: 0,67

G/T: 17,2

Gain: 38,2 dBi @11,3 GHz

Offset angle: 21 °

Satellite positions: Eutelsat 13° east, ASTRA 19,2° east

Mast Ø: 65 mm max.

Feed reception: for UNYSAT-Universal-LNB

SCOPE OF DELIVERY

Satellite dish, 2x Unysat V/H LNB in a weatherproof housing, AZ/EL mount (with Multifeed-mount), 1x TechniSwitch 2/1 DiSEqC switch, screws, tools, instruction manual

Test Results EUTELASTRASAT 850, 2 participant



Zweiter Platz in der
Kategorie Sat-Anlagen bei
der Leserwahl zum König-
Kunde-Award 2014
(Camping, Cars & Caravans)