



TECHNIVISION 22 ST

Versatile LCD digital television set with 22" wide screen and integrated digital receiver for satellite reception and digital antenna reception (DVB-T)

EAN	Colour	Item no.	Weight (Box)	Weight	Unit without stand (W x H x D)	Device (W x H x D)	Box
4019588226432	black	5022/6403	8 kg	7 kg	530 x 360 x 85 mm	53 x 41,5 x 20,5 cm	59,5 x 47,3 x 23,4 cm

AMBIENT OPERATING CONDITIONS

Humidity: 10 75 %

Ambient temperature: 5 35 °C

LNB CONTROL

Current consumption: 400 mA

Vertical: <14 V without load, > 11.5 V at 400 mA
V

DiSEqC: DiSEqC 1.0 / DiSEqC 1.2 Sat Channel
Router

Horizontal: <20 V without load, > 17.2 V at 400
mA / LNB shut-off standby mode V

Band switch: 22 kHz

TECHNISAT ADDED VALUE SERVICES

AUTOINSTALL: Yes

AUDIO

Speakers: 2 W

CONNECTIONS

HDMI™ (in): 1

Common Interface (CI): 1

VGA: Yes

Scart: 1

S Video: Yes

F socket: 1

DECRYPTION SYSTEM

CI: Yes

DIMENSIONS / WEIGHT

Weight without stand: 5,9 kg

Set width without stand: 530 mm

Set height without stand: 360 mm

Set depth without stand: 85 mm

DISPLAY

Size (cm): 55

Format: 16:9

Contrast ratio: 700:1

Brightness: 400 cd/m²

Response time: 5 ms

Angle of view: 150° V / 160° H

Freeze frame: Yes

Zoom: Yes

Resolution (vertical and horizontal): 1366 x 768

Type: TFT-LCD

SD: Yes

Size (inches): 22

HANDLING/COMFORT

Alarm: Yes

Sleep timer: Yes

HOTEL MODE

Radio mode: Yes

Mixing of channel slots: Yes

MATERIALS CONTAINED

Lead: Yes

OTHER FEATURES

OSD languages: Dutch, Polish, Czech, German, Italian, Turkish, Hungarian, English, Russian, Spanish, Greek, Swedish, Portuguese, French

Total programme memory: 4.000

POWER CONSUMPTION

Energy class: D

Standby LED: 0,45 W

In operation: 50 W

annual energy consumption when switched on: 73 kilowatt hour per annum

Off status:

Power switch: Yes

POWER SUPPLY

Nominal voltage: 230 V

Frequency: 50 Hz

Mains adapter: internal

TUNER

Tuner type: DigitalSat und DVB-T-Empfangstuner

DVB-S tuner: 1

DVB-T Tuner: 1

Analogue UHF/VHF/CATV tuner: 1

Input impedance: 75 Ω

Reception on: SD (MPEG-2)

TECHNIROUTER ready: Yes

TUNER - ANALOGUE

Video standards: PAL, SECAM

Reception range: 46 860 MHz

TUNER - SAT

Viterbi rates: 1/2, 2/3, 3/4, 5/6, 7/8

FEC: Viterbi and Reed-Solomon

Reception range: 950 ... 2.150 MHz

DVB-S: 1 ... 45

DVB-S: QPSK

TUNER - TERRESTRIAL

Bitrate: 4 32

Voltage supply: 0,05 V

Demodulation: COFDM

Power supply: 5 A

Transmission mode: 2k/8k

Reception range 2: 470 ... 860 MHz

Reception range 1: 174 ... 230 MHz

WALL BRACKET

VESA wall mounting standards: VESA 100 x 100

SCOPE OF DELIVERY

TechniVision 22 ST, Remote control, Power cable