



## TECHNISWITCH 5/8 G2

Multi-switch system with connection possibility of 4 levels for distribution to up to 24 participants

EAN	Colour	Item no.	Weight (Box)	Weight	Device (W x H x D)	Box
4019588353596	blue/yellow	3235/3259	600 g	300 g	17,2 x 11,2 x 3,3 cm	17,5 x 13,4 x 10,5 cm

### TOP FEATURES

- DAB+ and FM radio with RDS – Enjoy noise-free reception with DAB+ digital radio or listen to your favorite stations via classic FM radio with RDS and PLL technology
- The professional system for Quattro LNB features 4 satellite inputs, 1 terrestrial input, and 8 outputs
- Without attenuation in the satellite range, with tilt equalization.
- Note: TECHNISYSTEM components are not compatible with TECHNISWITCH parts

### AMBIENT OPERATING CONDITIONS

Ambient temperature: -25 ... 55 °C

### AMPLIFICATION

Sat: -2 ... 3 dB

Terrestrial: -4 ... -1 dB

### DECOUPLING

Output: > 35 dB

**GENERAL CHARACTERISTICS**

Top features: For distribution of one satellite position

Top features: Up to 24 subscribers can be connected

Top features: For connecting a Quattro LNB

Top features: Up to 100 m distribution length due to inclination compensation

Top features: Energy saving - no mains adapter for operation

Top features: No attenuation in satellite range

**POWER SUPPLY**

Nominal voltage: 100 ... 240 V

Frequency: 50 ... 60 Hz

Mains adapter: extern DC 15V/1,2A

**RECEPTION RANGE**

Sat: 950 ... 2.150 MHz

Terrestrial: 47 ... 862 MHz

**TECHNICAL DATA**

Satellite inputs: 4

Terrestrial input: 1

Outputs: 8

Distribution length: max. 100 m

**SCOPE OF DELIVERY**

TechniSwitch 5/8 G2, Power supply, manual