



TECHNISWITCH 5/8 G2

Multi-switch system with connection possibility of 4 levels for distribution to up to 24 participants

Colour	EAN	Item no.	Weight (Box)	Weight	Device (W x H x D)	Box
blue/yellow	4019588353596	3235/3259	600 g	300 g	17,2 x 11,2 x 3,3 cm	17,5 x 13,4 x 10,5 cm

AMBIENT OPERATING CONDITIONS

Ambient temperature: -25 ... 55 °C

GENERAL CHARACTERISTICS

Top Features: For distribution of one satellite position

Top Features: Up to 24 subscribers can be connected

Top Features: For connecting a Quatro LNB

Top Features: Up to 100 m distribution length due to inclination compensation

Top Features: Energy saving - no mains adapter for operation

Top features: No attenuation in satellite range

TECHNICAL DATA

Satellite inputs: 4

Terrestrial input: 1

Outputs: 8

Distribution length: max. 100 m

AMPLIFICATION

Sat: -2 ... 3 dB

Terrestrial: -4 ... -1 dB

POWER SUPPLY

Nominal voltage: 100 ... 240 V

Frequency: 50 ... 60 Hz

Mains adapter: extern DC 15V/1,2A

DECOUPLING

Output: > 35 dB

RECEPTION RANGE

Sat: 950 ... 2.150 MHz

Terrestrial: 47 ... 862 MHz

SCOPE OF DELIVERY

TechniSwitch 5/8 G2, Power supply, manual