



UNYSAT Quatro-Switch-LNB

Digital-LNB for four participants

EAN	Colour	Item no.	Weight (Box)	Weight	Device (W x H x D)	Box
4019588089808	grey	0000/8980	500 g	440 g	7,5 x 13 x 17,5 cm	10 x 22,5 x 19 cm

TOP FEATURES

For 4 participant

Special weatherproof housing for the exelent reception electronics

Suitable for all TechniSat SATMAN dishes

Quick and easy assembly without a retaining clamp

LOCAL OSCILLATOR

Low band: 9,75 GHz

High band: 10,6 GHz

Accuracy: ± 1 MHz

Temperature drift: ± 3 MHz

Phase noise: -75 @10kHz

LNB CONTROL

Vertical: 16 ... 19 V

Horizontal: 11,5 ... 14,5 V

Band switch: 22 kHz

AMBIENT OPERATING CONDITIONS

Humidity: 10 ... 90 %

Ambient temperature: -30 ... 60 °C

INPUT FREQUENCY RANGE

Low band: 10,7 ... 11,7 GHz

High band: 11,7 ... 12,75 GHz

NOISE FACTOR

Noise figure: 0,6 dB

OUTPUT FREQUENCY RANGE

Low band: 950 ... 1.950 MHz

High band: 1.100 ... 2.150 MHz

POWER SUPPLY

LNB voltage supply: 11,5 ... 19 V

Power consumption: max. 190 mA

TECHNICAL DATA

Outputs: 4

Feed reception: Für SATMAN

Impedance: 75 Ω

Connector type: F-Buchse

Amplification: 52 ... 65 dB

SCOPE OF DELIVERY

Test Results UNYSAT Quatro-Switch-LNB



Note: sehr gut | 92,1%

SATVISION (04/2011)