

UNYSAT Quatro-Switch-LNB

Digital-LNB for four participants

EAN	Colour	Item no.	Weight (Box)	Weight	Device (W x H x D)	Box
4019588089808	grey	0000/8980	500 g	440 g	7,5 x 13 x 17,5 cm	10 x 22,5 x 19 cm

TOP FEATURES

- For 4 participant
- Special weatherproof housing for the exelent reception electronics
- Suitable for all TechniSat SATMAN dishes
- Quick and easy assembly without a retaining clamp

LOCAL OSCILLATOR

- Low band: 9,75 GHz
- High band: 10,6 GHz
- Accuracy: ± 1 MHz
- Temperature drift: ± 3 MHz
- Phase noise: -75 @10kHz

LNB CONTROL

- Vertical: 16 ... 19 V
- Horizontal: 11,5 ... 14,5 V
- Band switch: 22 kHz

AMBIENT OPERATING CONDITIONS

- Humidity: 10 ... 90 %
- Ambient temperature: -30 ... 60 °C

INPUT FREQUENCY RANGE

- Low band: 10,7 ... 11,7 GHz
- High band: 11,7 ... 12,75 GHz

NOISE FACTOR

- Noise figure: 0,6 dB

OUTPUT FREQUENCY RANGE

- Low band: 950 ... 1.950 MHz
- High band: 1.100 ... 2.150 MHz

POWER SUPPLY
LNB voltage supply: 11,5 ... 19 V
Power consumption: max. 190 mA

TECHNICAL DATA
Outputs: 4
Connector type: F-Buchse
Impedance: 75 Ω
Amplification: 52 ... 65 dB
Feed reception: Für SATMAN

SCOPE OF DELIVERY

Test Results UNYSAT Quatro-Switch-LNB



Note: sehr gut | 92,1%
SATVISION (04/2011)