

DIGICORDER HD S2X Plus

HDTV satellite receiver with integrated hard disk (DVR)

Hard drive	EAN	Colour	Item no.	Weight (Box)	Weight	Device (W x H x D)	Box
160	4019588106727	black	0106/4720	2,9 kg	2,6 kg	37 x 6,5 x 22 cm	44,5 x 12 x 28 cm
500 GigaByte	4019588156722	black	0156/4720	3,9 kg	2,6 kg	37 x 6,5 x 22 cm	44,5 x 12 x 28 cm

TOP FEATURES

HDTV-Twin-Tuner

TECHNISAT ADDED VALUE SERVICES

AUTOINSTALL: Yes

HANDLING/COMFORT

Sleep timer: Yes

AMBIENT OPERATING CONDITIONS

Ambient temperature: 5 ... 35 °C

Humidity: 10 ... 75 %

DECRYPTION SYSTEM

Conax: Yes

CI: Yes

POWER CONSUMPTION

Standby LED: 1 W

In operation: 24 W

CONNECTIONS

HDMI™ (out): 1

Common Interface (CI): 2

Digital electric audio output (S/PDIF): Yes

Digital optical audio out: Yes

Audio out analogue (RCA): Yes (rechts / links)

YUV (component output): 1

Scart: 2

Video Cinch out: 1

Ethernet 10/100 (RJ-45): Yes (RJ-45)

F socket: 2

RS-232: 1

LNB CONTROL

Vertical: 14 V

Horizontal: 18 V

Band switch: 22 kHz

DiSEqC: 1.0 / 1.2 / Sat-CR

OTHER FEATURES

OSD languages: Greek, Czech, Dutch, Spanish, Swedish, French, Russian, Turkish, Norwegian, English, Danish, Italian, Polish

Total programme memory: 5.000

DISPLAY

Picture in Picture (PIP): Yes (2 x SD, 1 x SD u. 1 x HD)

Freeze frame: Yes

Zoom: Yes

HD: Yes

1080i: Yes

SD: Yes

720p: Yes

576p: Yes

576i: Yes

TUNER

Tuner type: DigitalSat

Reception on: HDTV (Mpeg-4+2)

TECHNIROUTER ready: Yes

Input impedance: 75 Ω

TUNER - SAT

Reception range: 950 ... 2.150 MHz

DVB-S: QPSK

DVB-S: 2 ... 45

DVB-S2: 8PSK-QPSK

FEC: Viterbi and Reed-Solomon

POWER SUPPLY

Frequency: 50 Hz

Nominal voltage: 180 ... 250 V

Mains adapter: internal

SCOPE OF DELIVERY

DigiCorder HD S2 X Plus
comfortable remote control with batteries
power cable
scart cable
instruction manual