HDTV 32

32 inch multimedia television set (Full-HD) with a discreetly designed front frame, integrated Dual HDTV multi-tuner and an integrated hard drive

EAN	Colour	Item no.	Weight (Box)	Weight	Unit without stand (W x H x D)	Device (W x H x D)	Box
4019588332300	black/silver metallic	5332/0306	25 kg	21 kg	805 x 620 x 115 mm	80,5 x 65,5 x 20 cm	101 x 80 x 31 cm
4019588332317	black/titanium metallic	5332/0316	25 kg	21 kg	805 x 620 x 115 mm	80,5 x 65,5 x 20 cm	101 x 80 x 31 cm
4019588332324	black/black	5332/0326	25 kg	21 kg	805 x 620 x 115 mm	80,5 x 65,5 x 20 cm	101 x 80 x 31 cm
4019588332119	black/high	5332/0611	24,5 kg	24,5 kg	805 x 620 x 115 mm	80,5 x 65,5 x 20 cm	101 x 80 x 31 cm
4019588332614	balck/andalusian	5332/0601	24,5 kg	24,5 kg	805 x 620 x 115 mm	80,5 x 65,5 x 20 cm	101 x 80 x 31 cm
4019588332621	black/tuscany	5332/0602	24,5 kg	24,5 kg	805 x 620 x 115 mm	80,5 x 65,5 x 20 cm	101 x 80 x 31 cm

TOP FEATURES

Dual-HDTV-Multituner zum Empfang von DigitalSat, Kabel und DVB-T ohne zusätzlichen Receiver	2-Wege-Lautsprecher im Bassreflexgehäuse	Integrierte 250-GB-Festplatte/Timeshift
2xCI-Schnittstelle und Conax Smartcard-Leser	Netzwerk- und USB-Schnittstelle	Standbild/Zoom/PiP/PaP/PaT

AMBIENT OPERATING CONDITIONS

- Humidity: 10 - 75 %
- Ambient temperature: 5 - 35 °C

LNB CONTROL

- Current consumption: 400 mA
- Band switch: 22 kHz
- Horizontal: <20 V without load, > 17.2 V at 400 mA / LNB shut-off standby mode V
- DiSEqC: DiSEqC 1.0 / DiSEqC 1.x Sat Channel Router
- Vertical: <14 V without load, > 11.5 V at 400 mA V

TECHNISAT ADDED VALUE SERVICES

- AUTOINSTALL: Yes

AUDIO

- Speakers: 2 x 2-way sound system with bass reflex
- AC3 Dolby Digital bitstream out: Yes

CONNECTIONS

- HDMI™ (in): 3
- Common Interface (CI): 2
- Smartcard reader: Yes
- Subwoofer output: Yes
- VGA: Yes
- YUV (component input): Yes
- Scart: 2
- S Video: Yes
- Video IN: 1
- Ethernet 10/100 (RJ-45): Yes (RJ-45)
- F socket: 2
- IEC-Connector: Yes
- RS-232:

DECRYPTION SYSTEM

- Conax: Yes
- CI: Yes

DIMENSIONS / WEIGHT

- Set depth without stand: 115 mm
- Set height without stand: 620 mm
- Set width without stand: 805 mm

DISPLAY

- Size (cm): 81 cm
- Format: 16:9
- Contrast ratio: 3.000:1
- Brightness: 500 cd/m²
- Picture in Picture (PIP): Yes (2 x SD, 1 x SD u. 1 x HD)
- Response time: 8 ms
- Angle of view: 178° / 178°
- Picture and Picture (PAP): Yes
- Freeze frame: Yes
- Zoom: Yes
- SD: Yes
- 1080i: Yes
- Resolution (vertical and horizontal): 1920 x 1080
- HD: Yes
- Type: TFT-LCD "Full HD"
- 720p: Yes
- Size (inches): 32

GENERAL CHARACTERISTICS

- Hard drive: 250 GigaByte

HANDLING/COMFORT

Clock: Yes

Alarm: Yes

Sleep timer: Yes

HOTEL MODE

Customisable start screen: Yes

Configurable on times: Yes

Energy card function: Yes

USB cloning function: Yes

Multimedia connectors: Yes

Menu locking: Yes

Radio mode: Yes

Mixing of channel slots: Yes

Multicode remote control: Yes

Fireproofed housing: Yes

MATERIALS CONTAINED

Lead: Yes

OTHER FEATURES

OSD languages: Russian, Turkish, Swedish, Italian, Spanish, Greek, Portuguese, Polish, English, French, Hungarian, Czech, German, Dutch

Total programme memory: 5.000

Regional channel selection: Yes

POWER CONSUMPTION

SFIplus updating: 43 W

Software update: 43 W

Energy class: D

Standby fast start: 34 W

Standby LED: 0,09 W

In operation: 114 W

annual energy consumption when switched on: 166 kilowatt hour per annum

Off status:

Power switch: Yes

POWER SUPPLY

Mains adapter: internal

Frequency: 50 Hz

Nominal voltage: 230 V

TUNER

Tuner type: Dual-HDTV-Multituner

DVB-S tuner: 2

DVB-C Tuner: 2

DVB-T Tuner: 2

Analogue UHF/VHF/CATV tuner: 2

Reception on: HDTV (Mpeg-4+2) SD (MPEG-2)

TECHNIROUTER ready: Yes

Input impedance: 75 Ω

TUNER - ANALOGUE

Video standards: PAL, SECAM

Reception range: 46 ... 860 MHz

TUNER - CABLE

Symbol rate: 1,7 ... 7

FEC: Reed-Solomon

Reception range: 47 ... 862 MHz

Demodulation: 16/32/64/128/256 QAM

TUNER - SAT

DVB-S: 1 ... 45

Reception range: 950 ... 2.150 MHz

DVB-S2: 10 ... 31

DVB-S: QPSK

FEC: Viterbi and Reed-Solomon

Viterbi rates: 1/2, 2/3, 3/4, 5/6, 7/8

DVB-S2: 8PSK - QPSK

TUNER - TERRESTRIAL

Reception range 2: 470 ... 860 MHz

Bitrate: 4 ... 32

Voltage supply: 0,05 V

Demodulation: COFDM

Reception range 1: 174 ... 230 MHz

Transmission mode: 2k/8k

Power supply: 5 A

WALL BRACKET

VESA wall mounting standards: VESA 400 x 200

SCOPE OF DELIVERY

HDTV 32 Plus, mains power cable, fully specified remote control, 2 batteries (1.5 V AAA), angled screwdriver, operating manual, quick-and-easy manual, guarantee documents

Test Results HDTV 32

Stromsparer
AudioVideoFoto (04/2009)

Testergebnis: Gut
AudioVideoFoto
(04/2009)