



HDTV 40 Plus

40 inch multimedia television set (Full-HD) with high-quality aluminium front frame and contrast pane comes equipped with Dual HDTV multi-tuner and digital video recorder (integrated hard drive)

| EAN | Colour | Item no. | Weight (Box) | Weight | Unit without stand (W x H x D) | Device (W x H x D) | Box |
|---------------|-----------------|-----------|--------------|--------|--------------------------------|------------------------|---------------------------|
| 4019588345003 | silver anodised | 5340/0500 | 36 kg | 36 kg | 1.005 x 715 x 110 mm | 100,5 x 78,5 x 20 cm | 122 x 89 x 32 cm |
| 4019588345164 | black anodised | 5340/0516 | 40 kg | 36 kg | 1.005 x 715 x 110 mm | 100,5 x 78,5 x 20 cm | 122 x 89 x 32 cm |
| 4019588345058 | platin anodised | 5340/0505 | 36 kg | 36 kg | 1.005 x 715 x 110 mm | 100,5 x 78,5 x 20 cm | 122 x 89 x 32 cm |
| 4019588344006 | silver | 5340/0400 | 34 kg | 34 kg | 1.005 x 715 x 110 mm | 1005,0 x 775,0 x 200,0 | 1220,0 x 880,0 x 320,0 mm |
| 4019588344167 | black | 5340/0416 | 34 kg | 34 kg | 1.005 x 715 x 110 mm | 1005,0 x 775,0 x 200,0 | 1220,0 x 880,0 x 320,0 mm |
| 4019588344051 | platin | 5340/0405 | 34 kg | 34 kg | 1.005 x 715 x 110 mm | 1005,0 x 775,0 x 200,0 | 1220,0 x 880,0 x 320,0 mm |

TOP FEATURES

Dual-HDTV-Multituner zum Empfang von DVB-S2, DVB-T und DVB-C inkl. HDTV

Front aus eloxiertem Aluminium und Kontrastscheibe

2xCI-Schnittstelle und Conax Smartcard-Leser

Standbild/Zoom/PiP/PaP/PaT

AMBIENT OPERATING CONDITIONS

Humidity: 10 - 75 %

Ambient temperature: 5 - 35 °C

AUDIO

AC3 Dolby Digital bitstream out: Yes

Speakers: 2 x 2-way sound system with bass reflex

DIMENSIONS / WEIGHT

Set depth without stand: 110 mm

Set height without stand: 715 mm

Set width without stand: 1.005 mm

LNB CONTROL

Current consumption: 400 mA

Vertical: <14 V without load, > 11.5 V at 400 mA
V

DiSEqC: DiSEqC 1.0 / DiSEqC 1.x Sat Channel
Router

Band switch: 22 kHz

Horizontal: <20 V without load, > 17.2 V at 400
mA / LNB shut-off standby mode V

CONNECTIONS

HDMI™ (in): 3

Common Interface (CI): 2

Smartcard reader: Yes

Subwoofer output: Yes

VGA: Yes

YUV (component input): Yes

Scart: 2

S Video: Yes

Video IN: 1

Ethernet 10/100 (RJ-45): Yes (RJ-45)

F socket: 2

IEC-Connector: Yes

RS-232:

DISPLAY

Size (cm): 102 cm

Format: 16:9

Contrast ratio: 3.000:1

Picture in Picture (PIP): Yes

Brightness: 500 cd/m²

Response time: 8 ms

Angle of view: 178° / 178°

Picture and Picture (PAP): Yes

Freeze frame: Yes

Zoom: Yes

720p: Yes

1080i: Yes

Type: TFT-LCD "Full HD"

SD: Yes

Resolution (vertical and horizontal): 1920 x 1080

HD: Yes

Size (inches): 40

TECHNISAT ADDED VALUE SERVICES

AUTOINSTALL: Yes

DECRYPTION SYSTEM

Conax: Yes

CI: Yes

GENERAL CHARACTERISTICS

Hard drive: 250 GigaByte

Appearance: brushed, eloxated Aluminium

HANDLING/COMFORT

Alarm: Yes

Sleep timer: Yes

Clock: Yes

OTHER FEATURES

OSD languages: Greek, Italian, German, Swedish, Hungarian, Portuguese, Czech, English, Polish, Turkish, Dutch, Spanish, Russian, French

Total programme memory: 5.000

Regional channel selection: Yes

TUNER

Tuner type: Dual-HDTV-Multituner

DVB-S tuner: 2

DVB-C Tuner: 2

DVB-T Tuner: 2

Analogue UHF/VHF/CATV tuner: 2

Input impedance: 75 Ω

Reception on: HDTV (Mpeg-4+2) SD (MPEG-2)

TECHNIROUTER ready: Yes

TUNER - SAT

DVB-S2: 8PSK - QPSK

FEC: Viterbi and Reed-Solomon

Viterbi rates: 1/2, 2/3, 3/4, 5/6, 7/8

DVB-S: QPSK

DVB-S: 1 ... 45

DVB-S2: 10 ... 31

Reception range: 950 ... 2.150 MHz

HOTEL MODE

Customisable start screen: Yes

Configurable on times: Yes

Energy card function: Yes

USB cloning function: Yes

Multimedia connectors: Yes

Menu locking: Yes

Radio mode: Yes

Mixing of channel slots: Yes

Multicode remote control: Yes

Fireproofed housing: Yes

POWER CONSUMPTION

SFIplus updating: 45 W

Software update: 45 W

Energy class: D

Standby fast start: 36 W

Standby LED: 0,55 W

In operation: 169 W

annual energy consumption when switched on:
247 kilowatt hour per annum

Off status:

Power switch: Yes

TUNER - ANALOGUE

Video standards: PAL, SECAM

Reception range: 46 ... 860 MHz

TUNER - TERRESTRIAL

Voltage supply: 0,05 V

Reception range 1: 174 ... 230 MHz

Reception range 2: 470 ... 860 MHz

Bitrate: 4 ... 32

Transmission mode: 2k/8k

Demodulation: COFDM

Power supply: 5 A

MATERIALS CONTAINED

Lead: Yes

POWER SUPPLY

Frequency: 50 Hz

Nominal voltage: 230 V

Mains adapter: internal

TUNER - CABLE

Symbol rate: 1,7 ... 7

Demodulation: 16/32/64/128/256 QAM

FEC: Reed-Solomon

Reception range: 47 ... 862 MHz

WALL BRACKET

VESA wall mounting standards: VESA 400 x 200

SCOPE OF DELIVERY

HDTV 40 Plus, Mains power cable, Fully specified remote control, Remoty remote control, 4 batteries (1.5 V AAA), Angled screwdriver, Operating manual, Quick-and-easy manual, Guarantee documents

Test Results HDTV 40 Plus

