



TECHNINET BS3

Professional digital head-station with integrated multi-switch system. With the TechniNet BS 3 you yourself decide which programmes are fed into your own cable network.

EAN	Colour	Item no.	Weight (Box)	Weight
4019588059474	white/red	0000/5947	10 kg	7,26 kg
4019588859456	white/red	8000/5945		
4019588165946	white/red	1600/5945		

CONFIGURATION, MONITORING

Network interface: keiner

Service connection: RJ25, serial, for TechniNet Programmer

GENERAL

Power supply: 100 ... 250 VAC / 50 ... 60 Hz

Power input: Max. 120 W

Nominal temperature range: 0 ... 45 °C

Relative humidity: 0 ... 80 %

EMV: EN50083-2, EN55022:2006+A1:2007, EN55024:1998+A1:2001+A2:2003, EN61000-3-2:2066, EN61000-3-3:2008

Security: VDE 0855-1, DIN EN 60728-11:2005

GENERAL CHARACTERISTICS

Top features: Kopfstation mit acht Steckplätzen für acht Karten

Top features: Mit integriertem Multischaltersystem 4/8 zum verteilen der ZF-Ebenen auf die Umsetzer-Karten

Top features: Programmierung über Kabelfernbedienung

Top features: Hochwertiges, effizientes Schaltnetzteil

Top features: Für TechniNet PAL 1 CI-Umsetzer, TechniNet AV/PAL-Umsetzer

Top features: Wandmontage

POWER CONSUMPTION

Power switch: Yes

POWER SUPPLY

Frequency: 50 ... 60 Hz

Nominal voltage: 230 V

Mains adapter: internal

RF OUTPUT

Reception range: 42 ... 862 MHz

input / output: F-socket

Impedance: 75 Ω

Output level: ≤ 96 (± 3 dB) @ 256-QAM typisch

SAT IF INPUT / MULTISWITCH

Reception range: 950 ... 2.150 MHz

input / output: F-socket

Impedance: 75 Ω

Input level: 50 ... 90 (Summenpegel)

LNB voltage supply: 13 / 18 V & 22kHz

LNB power supply: Max. 300 mA je Eingang

SCOPE OF DELIVERY

TechniNet BS3, Netzkabel, Abschlusswiderstände