



TECHNIVISION 22 C

Digital TV for receiving digital and analogue cable without the need for an additional receiver

EAN	Colour	Item no.	Weight (Box)	Weight	Unit without stand (W x H x D)	Device (W x H x D)	Box
4019588226425	black	5022/6402	8 kg	7 kg	530 x 360 x 85 mm	53 x 41,5 x 20,5 cm	59,5 x 47,3 x 23,4 cm
4019588224124	high/gloss	5022/6412	6 kg	6 kg	530 x 360 x 85 mm	53 x 41,5 x 20,5 cm	59,5 x 47,3 x 23,4 cm

AMBIENT OPERATING CONDITIONS

Ambient temperature: 5 35 °C

Humidity: 10 75 %

LNB CONTROL

Vertical: <14 V without load, > 11.5 V at 400 mA
V

Horizontal: <20 V without load, > 17.2 V at 400
mA / LNB shut-off standby mode V

DiSEqC: DiSEqC 1.0 / DiSEqC 1.2 Sat Channel
Router

Band switch: 22 kHz

Current consumption: 400 mA

TECHNISAT ADDED VALUE SERVICES

AUTOINSTALL: Yes

AUDIO

Speakers: 2 W

CONNECTIONS

HDMI™ (in): 1

Common Interface (CI): 1

Audio in/AUX in: Yes

VGA: Yes

Scart: 1

IEC-Connector: Yes

DECRYPTION SYSTEM

CI: Yes

DIMENSIONS / WEIGHT

Weight without stand: 5,9 kg

Set depth without stand: 85 mm

Set height without stand: 360 mm

Set width without stand: 530 mm

DISPLAY

Size (cm): 55

Format: 16:9

Contrast ratio: 700:1

Brightness: 400 cd/m²

Response time: 5 ms

Angle of view: 150° V / 160° H

Freeze frame: Yes

Zoom: Yes

Size (inches): 22

Resolution (vertical and horizontal): 1366 x 768

Type: TFT-LCD "Full HD"

SD: Yes

HANDLING/COMFORT

Alarm: Yes

Sleep timer: Yes

HOTEL MODE

Radio mode: Yes

MATERIALS CONTAINED

Lead: Yes

OTHER FEATURES

OSD languages: Czech, Russian, English, Turkish, Italian, Swedish, Greek, German, Polish, French, Hungarian, Spanish, Portuguese, Dutch

Total programme memory: 4.000

POWER CONSUMPTION

Energy class: C

Standby LED: 0,45 W

In operation: 48 W

annual energy consumption when switched on: 70 kilowatt hour per annum

Off status:

Power switch: Yes

POWER SUPPLY

Frequency: 50 Hz

Nominal voltage: 230 V

Mains adapter: internal

TUNER

Tuner type: DigitalKabel

DVB-C Tuner: 1

TECHNIROUTER ready: Yes

Reception on: SD (MPEG-2)

TUNER - CABLE

FEC: Reed-Solomon

Symbol rate: 1,7 7

Reception range: 47 862 MHz

Demodulation: 16/32/64/128/256 QAM

WALL BRACKET

VESA wall mounting standards: VESA 100 x 100

SCOPE OF DELIVERY

TechniVision 22 C, Remote control, Power cable