



TECHNIVISION 26 ST

26 inch LCD television with integrated digital satellite and DVB-T tuner with Common Interface

EAN	Colour	Item no.	Weight (Box)	Weight	Unit without stand (W x H x D)	Device (W x H x D)	Box
4019588266445	black	5026/6404	11,5 kg	8,2 kg	660 x 450 x 100 mm	66 x 49,5 x 20,5 cm	75,5 x 58,5 x 25 cm
4019588266438	black	5026/6403	9 kg	9 kg	660 x 450 x 100 mm	66 x 49,5 x 20,5 cm	75,5 x 58,5 x 25 cm

AMBIENT OPERATING CONDITIONS

Humidity: 10 75 %

Ambient temperature: 5 35 °C

LNB CONTROL

Current consumption: 400 mA

DiSEqC: DiSEqC 1.0 / DiSEqC 1.2 Sat Channel Router

Band switch: 22 kHz

Horizontal: <20 V without load, > 17.2 V at 400 mA / LNB shut-off standby mode V

Vertical: <14 V without load, > 11.5 V at 400 mA V

AUDIO

Speakers: 2 W

AC3 Dolby Digital bitstream out: Yes

CONNECTIONS

HDMI™ (in): 1

Common Interface (CI): 2

Subwoofer output: Yes

VGA: Yes

YUV (component input): Yes

Scart: 1

S Video: Yes

Video IN: 1

F socket: 1

RS-232:

DISPLAY

Size (cm): 66

Format: 16:9

Contrast ratio: 700:1

Brightness: 400 cd/m²

Response time: 5 ms

Angle of view: 150° V / 160° H

Freeze frame: Yes

Zoom: Yes

Type: TFT-LCD

Size (inches): 26

SD: Yes

Resolution (vertical and horizontal): 1366 x 768

MATERIALS CONTAINED

Lead: Yes

POWER SUPPLY

Mains adapter: internal

Frequency: 50 Hz

Nominal voltage: 230 V

DECRYPTION SYSTEM

CI: Yes

HANDLING/COMFORT

Sleep timer: Yes

Alarm: Yes

OTHER FEATURES

OSD languages: Czech, Polish, Hungarian, Greek, English, Dutch, Russian, German, Swedish, Spanish, Portuguese, French, Turkish, Italian

Total programme memory: 4.000

TUNER

Tuner type: DigitalSat und DVB-T-Empfangstuner

DVB-S tuner: 1

DVB-T Tuner: 1

Analogue UHF/VHF/CATV tuner: 1

Reception on: SD (MPEG-2)

Input impedance: 75 Ω

TECHNIROUTER ready: Yes

DIMENSIONS / WEIGHT

Set depth without stand: 100 mm

Weight without stand: 7 kg

Set height without stand: 450 mm

Set width without stand: 660 mm

HOTEL MODE

Radio mode: Yes

Mixing of channel slots: Yes

POWER CONSUMPTION

Energy class: D

Standby LED: 0,53 W

In operation: 83 W

annual energy consumption when switched on: 121 kilowatt hour per annum

Off status:

Power switch: Yes

TUNER - ANALOGUE

Reception range: 46 860 MHz

Video standards: PAL, SECAM

TUNER - SAT

DVB-S: QPSK

Reception range: 950 ... 2.150 MHz

DVB-S: 1 ... 45

FEC: Viterbi and Reed-Solomon

Viterbi rates: 1/2, 2/3, 3/4, 5/6, 7/8

TUNER - TERRESTRIAL

Reception range 2: 470 ... 860 MHz

Reception range 1: 174 ... 230 MHz

Voltage supply: 0,05 V

Transmission mode: 2k/8k

Power supply: 5 A

Bitrate: 4 32

Demodulation: COFDM

WALL BRACKET

VESA wall mounting standards: VESA 200 x 100

SCOPE OF DELIVERY

TechniVision 26 ST, Remote control, Power cable