



## Active 2-way tap 17/2A

Active 2-way tap for 4 orbital positions

EAN	Colour	Item no.	Weight (Box)	Weight	Device (W x H x D)	Box
4019588032705	silver	0000/3270	858 g	800 g	21,3 x 4,3 x 10,5 cm	23,1 x 10,7 x 6 cm

### AMBIENT OPERATING CONDITIONS

Ambient temperature: -25 ... 55 °C

### AMPLIFICATION

Sat: 3 ... 6 dB

Terrestrial: 5 dB einstellbar

### DECOUPLING

Output: 45 dB

Trunks: 50 dB

### GENERAL CHARACTERISTICS

Top Features: Gleiches Rastermass der F-Buchsen wie GIGASYSTEM 17/8

### POWER SUPPLY

Power consumption: typ. 300 mA @18V, je Abzweigegruppe

### RECEPTION RANGE

Sat: 950 ... 2.150 MHz

Terrestrial: 47 ... 862 MHz

### TECHNICAL DATA

Satellite inputs: 16

Terrestrial input: 1

### TRANSMISSION LOSS

Sat: -1,5 ... -1 dB

Terrestrial: -1,2 dB

### SCOPE OF DELIVERY

Active 2-way tap 17/2A, instruction manual