



TECHNIPRO RV 600-10E

Satellite pass-through socket for single-cable systems. Antenna socket with a 10 dB attenuation and electronic overload protection.

EAN	Colour	Item no.	Weight (Box)	Weight	Device (W x H x D)	Box
4019588031821	silver	0000/3182	96 g	1,4 g	7 x 7 x 2,5 cm	20,5 x 7,5 x 14,5 cm
4019588031821	silver	0000/3182	96 g	1,4 g	7 x 7 x 2,5 cm	20,5 x 7,5 x 14,5 cm

CONNECTOR TYPE

Radio: IEC connector (f)

TV: IEC connector (m)

SAT: F-socket

FREQUENCY RANGE

Radio: 87,5 ... 108 MHz

SAT: 950 ... 2.150 MHz

TV: 47...68/ 118 ... 862 MHz

SHIELDING FACTOR

47 - 300 MHz: ≥ 85 dB

300 - 470 MHz: ≥ 80 dB

470 - 950 MHz: ≥ 75 dB

950 - 2150 MHz: ≥ 55 dB

TAP LOSS

Radio: 11 dB

SAT: 10 dB

TV: 10 dB

TRANSMISSION LOSS

VHF: 1 dB

UHF: 1 dB

Sat: 1,9 dB

SCOPE OF DELIVERY

TechniPro RV 600-10E