



Universal-V/H-LNB

Digital-LNB for single-reception

EAN	Colour	Item no.	Weight (Box)	Weight	Device (W x H x D)	Box
4019588178946	grey	0017/8194	200 g	120 g	5,8 x 5,8 x 11,3 cm	6,5 x 6,5 x 12 cm

LOCAL OSCILLATOR

Low band: 9,75 GHz

High band: 10,6 GHz

LNB CONTROL

Vertical: 11,5 ... 14 V

Horizontal: 16 ... 19 V

Band switch: 22 kHz

AMBIENT OPERATING CONDITIONS

Humidity: 10 ... 90 %

Ambient temperature: -30 ... 60 °C

INPUT FREQUENCY RANGE

Low band: 10,7 ... 11,7 GHz

High band: 11,7 ... 12,75 GHz

NOISE FACTOR

Noise figure: 0,7 dB

OUTPUT FREQUENCY RANGE

Low band: 950 ... 1.950 MHz

High band: 1.100 ... 2.150 MHz

POWER SUPPLY

LNB voltage supply: 11,5 ... 19 V

Power consumption: max. 190 mA

TECHNICAL DATA

Outputs: 1

Impedance: 75 Ω

Feed reception: 40 mm

Amplification: 50 ... 65 dB

Connector type: F-Buchse

SCOPE OF DELIVERY