



DIGIPAL T2/C HD

Combo-Receiver zum Empfang von DVB-C und DVB-T2 HD

EAN	Colour	Item no.	Weight (Box)	Weight	Device (W x H x D)	Box
4019588049383	anthracite	0000/4938	790 g	240 g	18,2 x 4 x 12,6 cm	30,5 x 7,4 x 17,5 cm
4019588149380	silver	0001/4938	790 g	240 g	18,2 x 4 x 12,6 cm	30,5 x 7,4 x 17,5 cm
4019588109384	anthracite	0010/4938	790 g	240 g	18,2 x 4 x 12,6 cm	30,5 x 7,4 x 17,5 cm

TOP FEATURES

DVB-T2 HD (H.265/HEVC), DVB-T2 (H.264) or DVB-T

Operation on 12V

ISI mode: simplified device control

Internetradiofunktion

Electronic program guide (EPG)

Internet radio function

TECHNISAT ADDED VALUE SERVICES

AUTOINSTALL: Yes

ISIPRO cable: Yes

CONNECTIONS

HDMI™ (out): 1

audio/video output analog (3.5 mm jack): Yes
TechniSat specific adapter set necessary
(available at 0000/3649)

USB: 1 (USB 2.0)

Smartcard reader: Yes

Digital electric audio output (S/PDIF): Yes

Ethernet 10/100 (RJ-45): Yes

IEC-Connector: Yes

DECODER

Video decoder: MPEG-2 MP@HL/ML, H.264/MPEG-4 AVC, H.265/HEVC

Audio decoder: MPEG-1 & MPEG-2 Layer I, II, III

DECRYPTION SYSTEM

Irdeeto: Yes

DISPLAY

Freeze frame: Yes

SD: Yes

HD: Yes

1080p: Yes

1080i: Yes

720p: Yes

576p: Yes

576i: Yes

HANDLING/COMFORT

Teletext subtitles: Yes

Media Player: Yes

Alarm: Yes

Ideal for camping: Yes

Teletext: Yes

Sleep timer: Yes

OTHER FEATURES

OSD languages: English, German, French, Greek, Italian, Lithuanian, Dutch, Polish, Portuguese, Spanish, Czech, Turkish, Hungarian, Swedish

POWER CONSUMPTION

Standby LED: < 0,3 W

In operation: 4,7 W

POWER SUPPLY

Frequency: 50 Hz

Mains adapter: extern DC 12 V / 1,5 A

Nominal voltage: 230 V

READY FOR RECEPTION

freenetTV: Yes

SUPPORTED FORMATS & CODECS

Video-Formats: MKV, MP4, MOV, MPG, MTS, TS, TS4, VOB, M2TS, AVI

Picture-Formats: BMP, JPEG, PNG, TIFF

Audio-Formats: AAC, MP3, M4A, MP2

TUNER

Tuner type: Single-Tuner

DVB-C Tuner: 1

Tuner DVB-T2: DVB-T2/HEVC (H.265)

DVB-T Tuner: 1

Reception on: HD-TV, SD-TV, radio

TUNER - CABLE

Reception range: 47 ... 862 MHz

Demodulation: 16 / 32 / 64 / 128 / 256 QAM

Symbol rate: 1,5 ... 7,2

FEC: Reed-Solomon (204, 188)

TUNER - TERRESTRIAL

Reception range 1: 174 ... 230 MHz

Reception range 2: 470 ... 862 MHz

Demodulation: COFDM / QPSK, 16-QAM, 64-QAM, 256-QAM

Transmission mode: 1k, 2k, 4k, 8k, 16k, 32k

Voltage supply: 5 V

Power supply: max. 0,03 A

SCOPE OF DELIVERY

DIGIPAL T2 HD, remote control TechniControl incl. batteries, power supply, HDMI cable, manual