



TECHNITOP HAV 30

CATV amplifier with 30/20 dB gain and return path of 5-65 MHz.

Colour	EAN	Item no.	Weight (Box)	Weight	Device (W x H x D)	Box
white	4019588131392	0001/3139	362 g	332 g	13,3 x 6,7 x 3,9 cm	14,2 x 9,7 x 5 cm

AMBIENT OPERATING CONDITIONS

Ambient temperature: -20 ... 50 °C

IP class: 20

Humidity: 10 ... 75 %

OUTPUT LEVEL

Standard IMA UHF: 111 dB

Standard IMA UHF: 111 dB

IMA DIN 45004B VHF: 102 dB

IMA DIN 45004B UHF: 102 dB

AMPLIFICATION

Amplification: ≤ 30 dB

Return path: -2,5 dB

POWER REQUIREMENT

Operating voltage: 230 V

Power input: 4 W

GENERAL CHARACTERISTICS

Top features: Switchable gain 20/30 dB

Top features: Gain and slope adjustable

Top features: Return channel compatible (DOCSIS)

POWER SUPPLY

Frequency: 50 Hz

Effective output: 3,5 W

Mains adapter: internal

Nominal voltage: 230 V ~

RANGE OF ADJUSTMENT

Attenuator: 0 ... 17 dB

Equaliser: 0 ... 17 dB

TECHNICAL DATA

Frequency range: 87 ... 862 MHz

Output level: 97 (CTB, CTO, EN 50083-3)

Frequency range return path: 5 ... 65 MHz

Amplification: 20 / 30 dB switchable

Noise factor: $\leq 8,5$ dB

Shielding factor: ≥ 75 dB EN 50083-2 (Class A)

Connector type: F female

Impedance: 75 Ω

Return loss: ≥ 10 dB

SCOPE OF DELIVERY

TECHNITOP HAV 30; installation manual