

Universal SCR 4+4 LNB

Satellite channel router LNB with 4 legacy outputs

Colour	EAN	Item no.	Weight (Box)	Weight	Device (W x H x D)	Box
black	4019588083882	0000/8388	282 g	250 g	5,4 x 5,4 x 12,4 cm	11 x 13,3 x 6 cm

TOP FEATURES

- 4 receivers with SCR support can be connected
- 4 receivers can be connected via legacy output
- SCR protocol according to EN 50494
- F connectors
- Feed ø 40 mm
- LTE interference-safe

LOCAL OSCILLATOR

- Accuracy: ± 1 MHz
- Temperature drift: ± 2 MHz
- Phase noise: -83 @10kHz
- High band: 10,6 GHz
- Low band: 9,75 GHz

FILTER-NAVIGATION

- Number participants: 8
- Number satellites: 1

LNB CONTROL

- Vertical: 11,5 ... 15,5 V
- Horizontal: 16 ... 19 V
- Band switch: 22 kHz
- DiSEqC: EN50494

AMBIENT OPERATING CONDITIONS

- Ambient temperature: -40 ... 70 °C
- Humidity: 10 ... 95 %

INPUT FREQUENCY RANGE

- Low band: 10,7 ... 11,7 GHz
- High band: 11,7 ... 12,75 GHz

NOISE FACTOR

- Noise figure: typ. 0,7 dB

OUTPUT FREQUENCY RANGE

- High band: 1.100 ... 2.150 MHz
- Low band: 950 ... 1.950 MHz

POWER SUPPLY

- Power consumption: 250 mA

PREPARED FOR

- Number of orbit positions: 1
- Number of clients: 8

SINGLE-CABLE OUTPUT

Output frequency: 950 ... 2.150 MHz

Number of output channels: 4

Frequency of the output channels: 1284, 1400, 1516, 1632 MHz

TECHNICAL DATA

Outputs: 5 ; 1x SCR, 4x Legacy

Connector type: F female

Feed reception: 40 mm

Amplification: 57 dB

Impedance: 75 Ω

SCOPE OF DELIVERY

Universal-SCR 4+4 LNB