



2 way satellite splitter

for the 2-fold distribution or merger of Sat signals

Colour	EAN	Item no.	Weight (Box)	Weight	Device (W x H x D)	Box
silver	4019588223202	0022/3220	60 g	41 g	5,5 x 1,7 x 5,4 cm	5,5 x 1,7 x 5,4 cm

TOP FEATURES

DC power pass

DiSEqC-compatible

TECHNIROUTER-compatible

DECOUPLING

5 - 862 MHz: Typ. 16 dB (< 40 MHz = 8 dB)

950 - 1750 MHz: Typ. 15 dB

1750 - 2150 MHz: Typ. 12 dB

RETURN LOSS

5 - 862 MHz: Typ. 16 dB

950 - 1750 MHz: Typ. 12 dB

1750 - 2150 MHz: Typ. 12 dB

TECHNICAL DATA

Input: 1

Outputs: 2

Frequency range: 5 ... 2.400 MHz

Shielding factor: ≥ 75 dB EN 50083-2 (Class A)

Connector type: F female

Impedance: 75 Ω

TRANSMISSION LOSS

5 - 862 MHz: Typ. 4 dB (± 1)

950 - 1750 MHz: Typ. 5 dB ($\pm 1,5$)

1750 - 2150 MHz: Typ. 7 dB (± 2)

SCOPE OF DELIVERY

2-way satellite splitter