

# TechniSat



## TECHNITENNE 60 with Twin-LNB

60 cm digital satellite antenna made of steel with twin LNB

Colour	EAN	Item no.	Weight	Device (W x H x D)	Box
anthracite	4019588136823	1360/2882	2,1 kg	56 x 65 x 50 cm	58 x 65,4 x 13,4 cm
light/gray	4019588106826	1060/2882	2,1 kg	56 x 65 x 50 cm	58 x 65,4 x 13,4 cm

### TOP FEATURES

- Powerful: digital 60 cm satellite dish with 40 mm Twin LNB for easy connection of up to two receivers or TVs for optimal satellite reception with a wide variety of programs
- Easy installation: With the integrated mast mount (32 – 56 mm) and the included manual, mounting the satellite dish is quick and easy
- Versatile: The stable satellite system can be mounted in various ways on the house. Suitable for roof or wall installation or mounting on a special ground stand
- Reception: The satellite dish with LNB is Ultra-HD compatible and provides stable, razor-sharp reception of one orbital position for up to two receivers/users

<b>SONSTIGES</b>	<b>LOCAL OSCILLATOR</b>	<b>LNB CONTROL</b>
bf_filter_austattung: with LNB	Low band: 9,75 GHz	Vertical: 10,5 ... 14 V
bf_filter_number_of_participants: 2	High band: 10,6 GHz	Horizontal: 16 ... 23 V
bf_filter_diameter: 60 cm	Accuracy: $\pm 1$ MHz	Band switch: 22 kHz
bf_filter_number_satellites: 1	Temperature drift: $\pm 0,5$ MHz	
	Phase noise: -75 @10kHz	
<b>GENERAL CHARACTERISTICS</b>	<b>INPUT FREQUENCY RANGE</b>	<b>OUTPUT FREQUENCY RANGE</b>
Material: steel	Low band: 10,7 ... 11,7 GHz	Low band: 950 ... 1.950 MHz
Material strength: 0,5 mm	High band: 11,7 ... 12,75 GHz	High band: 1.100 ... 2.150 MHz
Coating: painted		
<b>TECHNICAL DATA</b>	<b>SCOPE OF DELIVERY</b>	
Rated measurement: 0,56 m	TECHNITENNE 60, Universal-Twin-LNB, Montageanleitung	
F/D: 0,49		
G/T: 14,5		
Gain: 35,3 dBi @11.30GHz		
Offset angle: 27,77 °		
Mast Ø: 32 ... 50 mm		
Feed reception: 40 mm		
Outputs: 2		
Connector type: F female		
Impedance: 75 Ω		
Amplification: 58 ... 64 dB (LNB)		