



SKYRIDER DOME Twin

Compact, mobile DigitalSat system with twin LNB

| Colour | EAN | Item no. | Weight (Box) | Weight | Device (W x H x D) | Box |
|--------|---------------|-----------|--------------|--------|--------------------|-----------------------|
| Weiß | 4019588245808 | 0245/1580 | 7,3 kg | 4,7 kg | 45 x 41 x 45 cm | 47,7 x 54,1 x 47,7 cm |

SONSTIGES

bf_filter_number_satellites: 4

bf_filter_number_of_participants: 2

LOCAL OSCILLATOR

Low band: 9,75 GHz

High band: 10,6 GHz

LNB CONTROL

DiSEqC: 1.0 / 1.1

Vertical: 10,5 ~ 14,5 V

Horizontal: 15,5 ~ 21 V

AMBIENT OPERATING CONDITIONS

IP class: X 6

Ambient temperature: -20 ... 60 °C

GENERAL CHARACTERISTICS

Material: plastic

Colour: white

HANDLING/COMFORT

Satellite search time: Bis zu 180 s (typisch)

INPUT FREQUENCY RANGE

Low band: 10,7 - 11,7 GHz

High band: 11,7 - 12,75 GHz

OUTPUT FREQUENCY RANGE

Low band: 950 - 1.950 MHz

High band: 1.100 - 2.150 MHz

POWER CONSUMPTION

In operation: 30 W max. (während der Satellitensuche)

POWER SUPPLY

Nominal voltage: DC 12 ... 24 V

Power consumption: 170 mA (LNB)

Effective output: 18 W / 1,5 A max.

PREPARED FOR

Number of clients: 2

Number of orbit positions: 4

TECHNICAL DATA

Outputs: 2

F/D: 0,23

G/T: 9,7

Gain: 31 dBi

Connector type: F socket

SCOPE OF DELIVERY

SKYRIDER Dome, instruction manual, controller, remote control, 2 x F-type SAT cable, 12 volt adapter cable