



SATMAN 65 PLUS with UNYSAT-Quattro-Switch-LNB

SATMAN external unit with pre-assembled AZ/EL mount, 65 cm Ø

EAN	Colour	Item no.	Weight (Box)	Weight
4019588898004	beige	2065/8980	6,6 kg	4,2 kg
4019588898035	slate/grey	2365/8980	6,6 kg	4,2 kg
4019588898042	brick/red	2465/8980	6,6 kg	4,2 kg
4019588898073	polar white	2765/8980	6,6 kg	4,2 kg
4019588898059	yellow with Smiley	2565/8980	6,6 kg	4,2 kg

TOP FEATURES

65 cm Spiegel aus erstklassigem Aluminium
(beidseitig pulverbeschichtet)

1 bis 4 Teilnehmer

1 Orbitposition (z. B. Astra 19,2° Ost)

Optimal für Wand- und Dachmontage

LNB mit Wetterschutzgehäuse

LOCAL OSCILLATOR

Low band: 9,75 GHz

High band: 10,7 GHz

LNB CONTROL

Vertical: 11,5 - 14,5 V

Horizontal: 16 - 19 V

GENERAL CHARACTERISTICS

Material: Aluminium

Material strength: 1,5 mm

Coating: Powder-coated on both sites

INPUT FREQUENCY RANGE

Low band: 10,7 ... 11,7 GHz

High band: 11,7 ... 12,75 GHz

NOISE FACTOR

Lower frequency range: 0,6 dB max.

Upper frequency range: 0,6 dB max.

OUTPUT FREQUENCY RANGE

Low band: 950 ... 1.950 MHz

High band: 1.100 ... 2.150 MHz

TECHNICAL DATA

F/D: 0,69

G/T: 14,5

Offset angle: 27 °

Gain: 35,7 dBi @11,3 GHz

Mast Ø: 65 mm max.

Feed reception: for UNYSAT-Universal-LNB

SCOPE OF DELIVERY

Satellite dish antenna SATMAN 65, AZ/EL bracket mount, UNYSAT-Quattro-Switch-LNB, screws, installation instructions