



SATMAN 850 PLUS with UNYSAT-Twin-LNB

SATMAN external unit with pre-assembled AZ/EL mount, 85 cm Ø

EAN	Colour	Item no.	Weight (Box)	Weight	Device (W x H x D)	Box
4019588858824	beige	6085/8882	8,8 kg	5,2 kg	85 x 87 cm	88 x 95 x 24 cm
4019588858220	fir/green	6285/8882	8,8 kg	5,2 kg	85 x 87 cm	88 x 95 x 24 cm
4019588858206	slate/grey	6385/8882	8,8 kg	5,2 kg	85 x 87 cm	88 x 95 x 24 cm
4019588858244	brick/red	6485/8882	8,8 kg	5,2 kg	85 x 87 cm	88 x 95 x 24 cm
4019588858275	polar white	6785/8882	8,8 kg	5,2 kg		
4019588588820	yellow with Smiley	6585/8882	8,8 kg	5,2 kg	85 x 87 cm	87 x 95 x 24 cm
4019588489820	brick/red	6485/9882	8,8 kg	5,2 kg	89 x 85 x 7,5 cm	92,75 x 88 x 23,5 cm
4019588789821	polar white	6785/9882	8,8 kg	5,2 kg	89 x 85 x 7,5 cm	92,75 x 88 x 23,5 cm
4019588589827	yellow with Smiley	6585/9882	8,8 kg	5,2 kg	89 x 85 x 7,5 cm	92,75 x 88 x 23,5 cm
4019588089822	beige	6085/9882	8,8 kg	5,2 kg	89 x 85 x 7,5 cm	92,75 x 88 x 23,5 cm
4019588389823	slate/grey	6385/9882	8,8 kg	5,2 kg	89 x 85 x 7,5 cm	92,75 x 88 x 23,5 cm
4019588289826	fir/green	6285/9882	8,8 kg	5,2 kg	89 x 85 x 7,5 cm	92,75 x 88 x 23,5 cm

TOP FEATURES

85 cm dish made of first-class aluminum (powder-coated on both sides)

1 or 2 users

1 orbit position (e.g. Astra 19.2 ° East)

Ideal for wall and roof mounting

LNB with weatherproof housing

LOCAL OSCILLATOR

Low band: 9,75 GHz

High band: 10,7 GHz

LNB CONTROL

Vertical: 11,5 - 14,5 V

Horizontal: 16 - 19 V

GENERAL CHARACTERISTICS

Material: Aluminium

Material strength: 1,6 mm

Coating: Powder-coated on both sites

Colour: beige, polar white, slate-grey, brick red, fir green, yellow with smiley

INPUT FREQUENCY RANGE

Low band: 10,7 ... 11,7 GHz

High band: 11,7 ... 12,75 GHz

NOISE FACTOR

Lower frequency range: 0,6 dB max.

Upper frequency range: 0,6 dB max.

OUTPUT FREQUENCY RANGE

Low band: 950 ... 1.950 MHz

High band: 1.100 ... 2.150 MHz

PREPARED FOR

Number of clients: 2

Number of orbit positions: 1

TECHNICAL DATA

Rated measurement: 0,85 m

F/D: 0,67

G/T: 17,2

Offset angle: 21 °

Gain: 38,2 dBi @11,3 GHz

Mast Ø: 65 mm max.

Feed reception: for UNYSAT-Universal-LNB

SCOPE OF DELIVERY

Satellite dish antenna SATMAN 850, AZ/EL bracket mount, LNB in weather-proof housing, screws, installation instructions

Test Results SATMAN 850 PLUS with UNYSAT-Twin-LNB



Note: Gut | 88,7 %
SATVISION (04/2012)



Leserwahl König Kunde
Award - 2. Platz in der
Kategorie Sat-Anlagen
(Camping, Cars &
Caravans)