Inklusive Fernbedienung



CABLESTAR 400

Stereo radio for unencrypted digital radio programs via cable

Colour	EAN	Item no.	Weight (Box)	Weight	Device (W x H x D)	Box
black	4019588139435	0010/3943	4,09 kg	3,13 kg	38 x 13,5 x 18 cm	48 x 18,5 x 21,5 cm

TOP FEATURES

- Reception of unencrypted, digital radio programs via DVB-C
- Top quality OLED display
- Time display
- Save up to 20 of your favorite stations
- 2 x 10 W stereo system powered by ELAC
- Supports the audio code format AAC-LC

FILTER-NAVIGATION

- Reception type: Cable radio
- Features: Alarm clock
- Connections: AUX IN
- Operating mode: Mains operation

AMBIENT OPERATING CONDITIONS

- Humidity: 5 - 90 % relative air humidity (non-condensing)
- Ambient temperature: 5 - 35 °C

BLUETOOTH VERSION & PROFILE

- AVRCP (Audio Video Remote Control Profile): Yes
- A2DP (Advanced Audio Distribution Profile): Yes

CONNECTIONS

- Audio in/AUX in: Yes
- IEC-Connector: Yes
- Headphone connection jack (3,5 mm): 1
- DC IN: 1

DECODER

- Audio decoder: MPEG-1 & MPEG-2 layer I, II

DISPLAY

- Type: OLED

FUNCTIONS

MP3 playback via USB: Yes

USB charging function: Yes

CD player with MP3: Yes (mit Resume-Funktion)

HANDLING/COMFORT

Clock: Yes

Alarm: Yes

Snooze: Yes

Remote control: Yes

LOUDSPEAKERS

Output performance: 20 W (RMS)

Stereo speakers: Yes

Stereo: 2 x 10 W

Equalizer: Yes

ELAC-Speaker: Yes

NETWORK & COMMUNICATION

Bluetooth: Yes

OTHER FEATURES

OSD languages: English, German, French, Italian

POWER CONSUMPTION

Standby: 0,35 W

Power consumption in standby mode with active network connection: 0,35 W

In operation: 34 W max.

POWER SUPPLY

Nominal voltage: 230 V

Frequency: 50 Hz

Mains adapter: DC 12V / 3000 mA

Type of power supply: External

RADIO / RECEPTION

Aerial: DAB / FM telescopic antenna (replaceable)

STREAMING

Bluetooth audio streaming: Yes

SUPPORTED FORMATS & CODECS

AAC: Yes (ab SW V00.17)

TUNER

Tuner type: Digital cable

DVB-C Tuner: 1

Cable radio: Yes

Reception on: DVB radio

TUNER - CABLE

Reception range: 50 ... 858 MHz

Demodulation: 64 / 256 QAM

Symbol rate: 2 ... 7

FEC: Reed-Solomon (204, 188)

SCOPE OF DELIVERY

CABLESTAR 400, remote control, power supply, user manual