



## On/Off switch flush mount, G

Compatible with Gira switch ranges

EAN	Colour	Item no.	Weight (Box)	Weight	Device (W x H x D)	Box
4019588194991	light grey	0100/9499	130 g	70 g	7 x 7 x 4,5 cm	11,5 x 10,5 x 5,8 cm

### TOP FEATURES

Integration/control with TechniSat CONNECT

Device for flush mounting in standard device boxes

Compatible with Gira switch ranges

Measuring of energy consumption

Integrated scene control

Integrated Z-Wave™ repeater function

Electronic overload protection

### AMBIENT STORAGE CONDITIONS

Temperature: -20 ... 60 °C

Humidity: 5 ... 90 %

### AMBIENT OPERATING CONDITIONS

IP class: 20

Ambient temperature: 5 ... 35 °C

Humidity: 10 ... 75 %

### FUNK COMMUNICATION

Telecommunication: Z-Wave Plus

Security S2: Yes

SmartStart: Yes

Range inside: max. 40 m

operating frequency: 868,42 MHz

Repeater function: Yes

### POWER SUPPLY

Frequency: 50 Hz ± 10 %

Nominal voltage: 230 V ± 10 %

Effective output: 1,15 W

Power consumption: < 2 mA (without load)

### SCOPE OF DELIVERY

Circuit-breaker insert, compensation frame, assembly instructions, fastening screws