



Dimmer flush mount, G

Compatible with Gira switch ranges

| EAN | Colour | Item no. | Weight (Box) | Weight | Device (W x H x D) | Box |
|---------------|------------|-----------|--------------|--------|--------------------|----------------------|
| 4019588100978 | light grey | 0100/9497 | 130 g | 70 g | 7 x 7 x 4,5 cm | 11,5 x 10,5 x 5,8 cm |

TOP FEATURES

Integration/control with TechniSat CONNECT

Device for flush mounting in standard device boxes

Compatible with Merten switch ranges

Measuring of energy consumption

Integrated scene control

Integrated Z-Wave™ repeater function

Electronic overload protection

AMBIENT STORAGE CONDITIONS

Temperature: -20 ... 60 °C

Humidity: 5 ... 90 %

AMBIENT OPERATING CONDITIONS

IP class: 20

Humidity: 10 ... 75 %

Ambient temperature: 5 ... 35 °C

FUNK COMMUNICATION

Telecommunication: Z-Wave Plus

Security S2: Yes

SmartStart: Yes

Range inside: max. 40 m

operating frequency: 868,42 MHz

Repeater function: Yes

POWER SUPPLY

Frequency: 50 Hz ± 10 %

Nominal voltage: 230 V ± 10 %

Effective output: 200 W

Power consumption: < 3 mA (without load)

SCOPE OF DELIVERY

Dimmer insert, compensation frame, assembly instructions, fastening screws