



4 way satellite splitter

For the 4-fold distribution of Sat signals

EAN	Colour	Item no.	Weight (Box)	Weight	Device (W x H x D)	Box
4019588223110	silver	0022/3111	114 g	100 g	8,5 x 5,5 x 1,8 cm	9 x 10 x 2,5 cm

DECOUPLING

5 - 862 MHz: Typ. 20 dB

950 - 1750 MHz: Typ. 20 dB

1750 - 2150 MHz: Typ. 20 dB

GENERAL CHARACTERISTICS

Top features: DC power pass

Top features: diode decoupled

Top features: DiSEqC-compatible

Top features: TECHNIROUTER-compatible

RETURN LOSS

5 - 862 MHz: Typ. 12 dB

950 - 1750 MHz: Typ. 10 dB

1750 - 2150 MHz: Typ. 10 dB

TECHNICAL DATA

Input: 1

Outputs: 4

Frequency range: 5 ... 2.400 MHz

Shielding Factor: ≥ 75 dB EN 50083-2 (Class A)

Connector type: F female

Impedance: 75 Ω

TRANSMISSION LOSS

5 - 862 MHz: Typ. 8 dB (± 1)

950 - 1750 MHz: Typ. 8 dB (± 1)

1750 - 2150 MHz: Typ. 9 dB (± 1)

SCOPE OF DELIVERY

4-way satellite splitter