



## 4 way satellite splitter

For the 4-fold distribution of Sat signals

Colour	EAN	Item no.	Weight (Box)	Weight	Device (W x H x D)	Box
silver	4019588223110	0022/3111	114 g	100 g	8,5 x 5,5 x 1,8 cm	9 x 10 x 2,5 cm

### DECOUPLING

5 - 862 MHz: Typ. 20 dB

950 - 1750 MHz: Typ. 20 dB

1750 - 2150 MHz: Typ. 20 dB

### GENERAL CHARACTERISTICS

Top features: DC power pass

Top features: diode decoupled

Top features: DiSEqC-compatible

Top features: TECHNIROUTER-compatible

### RETURN LOSS

5 - 862 MHz: Typ. 12 dB

950 - 1750 MHz: Typ. 10 dB

1750 - 2150 MHz: Typ. 10 dB

### TECHNICAL DATA

Input: 1

Outputs: 4

Frequency range: 5 ... 2.400 MHz

Shielding Factor:  $\geq 75$  dB EN 50083-2 (Class A)

Connector type: F female

Impedance: 75  $\Omega$

### TRANSMISSION LOSS

5 - 862 MHz: Typ. 8 dB ( $\pm 1$ )

950 - 1750 MHz: Typ. 8 dB ( $\pm 1$ )

1750 - 2150 MHz: Typ. 9 dB ( $\pm 1$ )

### SCOPE OF DELIVERY

4-way satellite splitter