



8 way satellite splitter

For the 8-fold distribution of Sat signals

EAN	Colour	Item no.	Weight (Box)	Weight	Device (W x H x D)	Box
4019588223103	silver	0022/3110	136 g	130 g	11,8 x 6 x 1,7 cm	14,5 x 10 x 1,7 cm

DECOUPLING

5 - 862 MHz: Typ. 22 dB

950 - 1750 MHz: Typ. 22 dB

1750 - 2150 MHz: Typ. 21 dB

TECHNICAL DATA

Input: 1

Outputs: 8

Frequency range: 5 ... 2.150 MHz

Shielding factor: ≥ 75 dB EN 50083-2 (Class A)

Connector type: F female

Impedance: 75 Ω

GENERAL CHARACTERISTICS

Top features: DC power pass

Top features: diode decoupled

Top features: DiSEqC-compatible

Top features: TECHNIROUTER-compatible

TRANSMISSION LOSS

5 - 862 MHz: Typ. 12 dB (± 1)

950 - 1750 MHz: Typ. 15 dB (± 1)

1750 - 2150 MHz: Typ. 18 dB (± 1)

RETURN LOSS

5 - 862 MHz: Typ. 9 dB

950 - 1750 MHz: Typ. 13 dB

1750 - 2150 MHz: Typ. 11 dB

SCOPE OF DELIVERY

8-way satellite splitter