



## DIGISPLITTER CE 2 S/T HD

for the 2-fold distribution or merger of Sat signals

EAN	Colour	Item no.
4019588079120	silber	0000/7912

### TOP FEATURES

DC power pass

### SONSTIGES

bf\_filter\_number\_of\_participants: 2

bf\_filter\_number\_satellites: 1

### DECOUPLING

5 - 862 MHz: Typ. 22 dB (< 40 MHz = 8 dB)

950 - 1750 MHz: Typ. 20 dB

1750 - 2150 MHz: Typ. 20 dB

### RETURN LOSS

5 - 862 MHz: Typ. 12 dB

950 - 1750 MHz: Typ. 12 dB

1750 - 2150 MHz: Typ. 10 dB

### TECHNICAL DATA

Input: 1

Outputs: 2

Frequency range: 5 ... 2.400 MHz

Shielding factor:  $\geq 75$  dB EN 50083-2 (Class A)

Connector type: F female

Impedance: 75  $\Omega$

### TRANSMISSION LOSS

5 - 862 MHz: Typ. 4,5 dB ( $\pm 1$ )

950 - 1750 MHz: Typ. 5 dB ( $\pm 1,5$ )

1750 - 2150 MHz: Typ. 6 dB ( $\pm 2$ )

### SCOPE OF DELIVERY

2-waY TV Sat splitter