



DIGISPLITTER CE 4 S/T HD

Quad splitter for distribution or combination of satellite, terrestrial and cable TV, as well as radio signals

EAN	Colour	Item no.
4019588079144	silber	0000/7914

TOP FEATURES

DC power pass

SONSTIGES

bf_filter_number_of_participants: 2

bf_filter_number_satellites: 1

DECOUPLING

5 - 862 MHz: Typ. 20 dB (< 40 MHz = 8 dB)

950 - 1750 MHz: Typ. 20 dB

1750 - 2150 MHz: Typ. 20 dB

RETURN LOSS

5 - 862 MHz: Typ. 12 dB

950 - 1750 MHz: Typ. 12 dB

1750 - 2150 MHz: Typ. 10 dB

TECHNICAL DATA

Input: 1

Outputs: 4

Frequency range: 5 ... 2.400 MHz

Shielding factor: ≥ 75 dB EN 50083-2 (Class A)

Connector type: F female

Impedance: 75 Ω

TRANSMISSION LOSS

5 - 862 MHz: Typ. 8,5 dB (± 1)

950 - 1750 MHz: Typ. 9,5 dB ($\pm 1,5$)

1750 - 2150 MHz: Typ. 10,5 dB (± 2)

SCOPE OF DELIVERY

4-way TV Sat splitter