



UNIX Single LNB

High-quality converter for satellite installations with one receiver.

| EAN | Colour | Item no. |
|---------------|--------------|------------|
| 4019588768017 | beige/orange | 76-4801-00 |

TOP FEATURES

Top-class reception performance for HD and UHD signals

Simple and quick assembly

High quality housing resistant to difficult weather conditions

Very low noise figure

Low power consumption

LOCAL OSCILLATOR

Low band: 9,75 GHz

High band: 10,6 GHz

LNB CONTROL

Vertical: 10,5 ... 14 V

Horizontal: 16 ... 19 V

Band switch: 22 kHz

AMBIENT OPERATING CONDITIONS

Humidity: 10 ... 90 %

Ambient temperature: -30 ... 70 °C

INPUT FREQUENCY RANGE

Low band: 10,7 ... 11,7 GHz

High band: 11,7 ... 12,75 GHz

NOISE FACTOR

Noise figure: 0,1 dB

OUTPUT FREQUENCY RANGE

Low band: 950 ... 1.950 MHz

High band: 1.100 ... 2.150 MHz

POWER SUPPLY

LNB voltage supply: 10,5 ... 19 V

Power consumption: max. 120 mA

TECHNICAL DATA

Outputs: 1

Impedance: 75 Ω

Amplification: 55 dB

Feed reception: 40 mm

Connector type: F-connector

SCOPE OF DELIVERY