



UNIX Twin LNB

High-quality twin converter for satellite installations with two receivers

EAN	Colour	Item no.
4019588768024	beige/orange	76-4802-00

TOP FEATURES

Top-class reception performance for HD and UHD signals

Very low noise figure

Simple and quick assembly

Ideal for a TWIN decoder

High quality housing resistant to difficult weather conditions

Low power consumption

LOCAL OSCILLATOR

Low band: 9,75 GHz

High band: 10,6 GHz

LNB CONTROL

Vertical: 10,5 ... 14 V

Horizontal: 16 ... 19 V

Band switch: 22 kHz

AMBIENT OPERATING CONDITIONS

Humidity: 10 ... 90 %

Ambient temperature: -30 ... 70 °C

INPUT FREQUENCY RANGE

Low band: 10,7 ... 11,7 GHz

High band: 11,7 ... 12,75 GHz

NOISE FACTOR

Noise figure: 0,1 dB

OUTPUT FREQUENCY RANGE

Low band: 950 ... 1.950 MHz

High band: 1.100 ... 2.150 MHz

POWER SUPPLY

LNB voltage supply: 10,5 ... 19 V

Power consumption: max. 150 mA

TECHNICAL DATA

Outputs: 2

Impedance: 75 Ω

Amplification: 55 dB

Connector type: F-Buchse

Feed reception: 40 mm

SCOPE OF DELIVERY