UNIX Single Gold

Digital-LNB for single-reception

EAN	Colour	Item no.
4019588768116	beige/orange	76-4811-00

TOP FEATURES

- Top-class reception performance for HD and UHD signals
- Simple and quick assembly
- High quality housing resistant to difficult weather conditions
- Very low noise figure
- Low power consumption

LOCAL OSCILLATOR

- Low band: 9,75 GHz
- High band: 10,6 GHz

LNB CONTROL

- Vertical: 10,5 ... 14 V
- Horizontal: 16 ... 19 V
- Band switch: 22 kHz

AMBIENT OPERATING CONDITIONS

- Ambient temperature: -30 ... 70 °C
- Humidity: 10 ... 90 %

INPUT FREQUENCY RANGE

- Low band: 10,7 ... 11,7 GHz
- High band: 11,7 ... 12,75 GHz

NOISE FACTOR

- Noise figure: 0,1 dB

OUTPUT FREQUENCY RANGE

- Low band: 950 ... 1.950 MHz
- High band: 1.100 ... 2.150 MHz

POWER SUPPLY

- LNB voltage supply: 10,5 ... 19 V
- Power consumption: max. 120 mA

TECHNICAL DATA

- Outputs: 1
- Feed reception: 40 mm
- Connector type: f-connector
- Amplification: 55 dB
- Impedance: 75 Ω

SCOPE OF DELIVERY