



# UNIX Single Gold

Digital-LNB for single-reception

EAN	Colour	Item no.
4019588768116	beige/orange	76-4811-00

## TOP FEATURES

Top-class reception performance for HD and UHD signals

Simple and quick assembly

High quality housing resistant to difficult weather conditions

Very low noise figure

Low power consumption

## LOCAL OSCILLATOR

Low band: 9,75 GHz

High band: 10,6 GHz

## LNB CONTROL

Vertical: 10,5 ... 14 V

Horizontal: 16 ... 19 V

Band switch: 22 kHz

## AMBIENT OPERATING CONDITIONS

Ambient temperature: -30 ... 70 °C

Humidity: 10 ... 90 %

## INPUT FREQUENCY RANGE

Low band: 10,7 ... 11,7 GHz

High band: 11,7 ... 12,75 GHz

## NOISE FACTOR

Noise figure: 0,1 dB

## OUTPUT FREQUENCY RANGE

Low band: 950 ... 1.950 MHz

High band: 1.100 ... 2.150 MHz

## POWER SUPPLY

LNB voltage supply: 10,5 ... 19 V

Power consumption: max. 120 mA

## TECHNICAL DATA

Outputs: 1

Feed reception: 40 mm

Connector type: F-connector

Amplification: 55 dB

Impedance: 75 Ω

## SCOPE OF DELIVERY