



UNIX Twin Gold

High-quality twin converter for satellite installations with two receivers

EAN	Colour	Item no.
4019588768123	beige/orange	76-4812-00

TOP FEATURES

Top-class reception performance for HD and UHD signals

Very low noise figure

Simple and quick assembly

Perfect for the TWIN decoder

High quality housing resistant to difficult weather conditions

Low power consumption

LOCAL OSCILLATOR

Low band: 9,75 GHz

High band: 10,6 GHz

LNB CONTROL

Vertical: 10,5 ... 14 V

Horizontal: 16 ... 19 V

Band switch: 22 kHz

AMBIENT OPERATING CONDITIONS

Humidity: 10 ... 90 %

Ambient temperature: -30 ... 70 °C

INPUT FREQUENCY RANGE

Low band: 10,7 ... 11,7 GHz

High band: 11,7 ... 12,75 GHz

NOISE FACTOR

Noise figure: 0,1 dB

OUTPUT FREQUENCY RANGE

Low band: 950 ... 1.950 MHz

High band: 1.100 ... 2.150 MHz

POWER SUPPLY

LNB voltage supply: 10,5 ... 19 V

Power consumption: max. 150 mA

TECHNICAL DATA

Outputs: 2

Impedance: 75 Ω

Connector type: F-connector

Amplification: 55 dB

Feed reception: 40 mm

SCOPE OF DELIVERY