

UNIX Twin Gold

High-qualitY twin converter for satellite installations with two receivers

Colour	EAN	Item no.
beige/orange	4019588768123	76-4812-00

TOP FEATURES

- Top-class reception performance for HD and UHD signals
- Simple and quick assembly
- High quality housing resistant to difficult weather conditions
- Very low noise figure
- Perfect for the TWIN decoder
- Low power consumption

NOISE FACTOR

- Noise figure: 0,1 dB

OUTPUT FREQUENCY RANGE

- Low band: 950 ... 1.950 MHz
- High band: 1.100 ... 2.150 MHz

INPUT FREQUENCY RANGE

- Low band: 10,7 ... 11,7 GHz
- High band: 11,7 ... 12,75 GHz

AMBIENT OPERATING CONDITIONS

- Humidity: 10 ... 90 %
- Ambient temperature: -30 ... 70 °C

LNB CONTROL

- Vertical: 10,5 ... 14 V
- Horizontal: 16 ... 19 V
- Band switch: 22 kHz

LOCAL OSCILLATOR

- Low band: 9,75 GHz
- High band: 10,6 GHz

TECHNICAL DATA

- Outputs: 2
- Impedance: 75 Ω
- Connector type: f-connector
- Amplification: 55 dB
- Feed reception: 40 mm

POWER SUPPLY

- LNB voltage supply: 10,5 ... 19 V
- Power consumption: max. 150 mA

SCOPE OF DELIVERY