

UNIX Quad Gold

High-qualitY Quad LNB for satellite installations with four receivers

Colour	EAN	Item no.	Device (W x H x D)	Box
beige/orange	4019588768147	76-4814-00	5 x 11,5 x 9 cm	9,5 x 12,5 x 7 cm

TOP FEATURES

- Top-class reception performance for HD and UHD signals
- Simple and quick assembly
- High quality housing resistant to difficult weather conditions
- Very low noise figure
- Ideal for installations with two TWIN receivers
- Up to 4 users
- Low power consumption

NOISE FACTOR

Noise figure: 0,1 dB

OUTPUT FREQUENCY RANGE

Low band: 950 ... 1.950 MHz

High band: 1.100 ... 2.150 MHz

INPUT FREQUENCY RANGE

Low band: 10,7 ... 11,7 GHz

High band: 11,7 ... 12,75 GHz

AMBIENT OPERATING CONDITIONS

Ambient temperature: -30 ... 70 °C

Humidity: 10 ... 90 %

LNB CONTROL

Vertical: 10,5 ... 14 V

Horizontal: 16 ... 19 V

Band switch: 22 kHz

LOCAL OSCILLATOR

Low band: 9,75 GHz

High band: 10,6 GHz

TECHNICAL DATA

Outputs: 4

Amplification: 55 dB

Connector type: f-connector

Feed reception: 40 mm

Impedance: 75 Ω

POWER SUPPLY

LNB voltage supply: 10,5 ... 19 V

Power consumption: max. 180 mA

SCOPE OF DELIVERY