



F Compression connector 7.0

Compression F connector for 7mm cable

Colour	EAN	Item no.	Device (W x H x D)	Box
silver	4019588133488	0001/3348	1 x 1 x 1 cm	1 x 1 x 1 cm

TOP FEATURES

High-end F connector

100% waterproof

Operational up to 3 GHz

Especially for COAXSAT 140-4.6 cables from TechniSat

Without inner sleeve - simplified assembly

Suitable for many RG6 coaxial cables

Assembly with compression pliers 0000/3339 from TechniSat

ATTENUATION

10 MHz: 0,02

100 MHz: 0,02

450 MHz: 0,03

800 MHz: 0,05

862 MHz: 0,04

1000 MHz: 0,06

1350 MHz: 0,11

2250 MHz: 0,11

RETURN LOSS

65 - 470 MHz: ≥ 34 dB

470 - 1800 MHz: ≥ 33 dB

1800 - 2450MHz: ≥ 33 dB

SHIELDING

30 - 1000 MHz: > 105 dB CoMeT

1000 - 2250 MHz: > 95 dB CoMeT

TECHNICAL DATA

Protection class: IPX8

Impedance: 75 Ω

Diameter dielectric: max. 4,6 mm

Diameter with coating: 6,8 ... 7 mm

TRANSFER IMPEDANCE

5MHz: < 5

30 MHz: < 2,5

SCOPE OF DELIVERY

Pack: 100 piece