



## F Compression connector 7.0

Compression F connector for 7mm cable

EAN	Colour	Item no.	Device (W x H x D)	Box
4019588133488	silver	0001/3348	1 x 1 x 1 cm	1 x 1 x 1 cm

### TOP FEATURES

High-end F connector

100% waterproof

Operational up to 3 GHz

Especially for COAXSAT 140-4.6 cables from TechniSat

Without inner sleeve - simplified assembly

Suitable for many RG6 coaxial cables

Assembly with compression pliers 0000/3339 from TechniSat

### ATTENUATION

10 MHz: 0,02

100 MHz: 0,02

450 MHz: 0,03

800 MHz: 0,05

862 MHz: 0,04

1000 MHz: 0,06

1350 MHz: 0,11

2250 MHz: 0,11

### RETURN LOSS

65 - 470 MHz:  $\geq 34$  dB

470 - 1800 MHz:  $\geq 33$  dB

1800 - 2450MHz:  $\geq 33$  dB

### SHIELDING

30 - 1000 MHz:  $> 105$  dB CoMeT

1000 - 2250 MHz:  $> 95$  dB CoMeT

**TECHNICAL DATA**

Protection class: IPX8

Impedance: 75  $\Omega$

Diameter dielectric: max. 4,6 mm

Diameter with coating: 6,8 ... 7 mm

**TRANSFER IMPEDANCE**

5MHz: < 5

30 MHz: < 2,5

**SCOPE OF DELIVERY**

Pack: 100 piece