

Universal-V/H-LNB with satellite finder

Digital LNB with 1 legacy output and satellite finder

Colour	EAN	Item no.	Weight (Box)	Weight	Device (W x H x D)	Box
black	4019588198944	0019/8194	120 g	102 g	12,9 x 5,7 x 5,7 cm	14 x 6,3 x 6,3 cm

TOP FEATURES

- For 1 participant
- F connectors
- Feed-ø 40 mm
- Integrated level meter and compass
- LTE interference-safe
- Optimised for camping: Quick alignment thanks to integrated level meter and compass

LOCAL OSCILLATOR

- Low band: 9,75 GHz
- High band: 10,6 GHz
- Accuracy: ± 1 MHz
- Temperature drift: ± 2,5 MHz
- Phase noise: -75 @10kHz

LNB CONTROL

- Vertical: 12 ... 14,5 V
- Horizontal: 16 ... 20 V
- Band switch: 22 kHz

AMBIENT OPERATING CONDITIONS

- Humidity: 10 ... 95 %
- Ambient temperature: -10 ... 60 °C

HANDLING/COMFORT

- SAT-Finder: Yes

INPUT FREQUENCY RANGE

- Low band: 10,7 ... 11,9 GHz
- High band: 11,7 ... 12,75 GHz

NOISE FACTOR

- Noise figure: typ. 0,9 dB

OUTPUT FREQUENCY RANGE

- Low band: 950 ... 1.950 MHz
- High band: 1.100 ... 2.150 MHz

POWER SUPPLY

- LNB voltage supply: 12 ... 20 V
- Power consumption: max. 150 mA

PREPARED FOR

- Number of orbit positions: 1
- Number of clients: 1

TECHNICAL DATA

Feed reception: 40 mm

Amplification: 56 ... 65 dB

Outputs: 1

Impedance: 75 Ω

Connector type: F

SCOPE OF DELIVERY

UNYSAT Universal-V/H-LNB with satellite finder