

DIGIDISH 33 mit Satfinder V/H-LNB

The DigiDish 33 is enormously high-performance for its size and takes up very little space

Colour	EAN	Item no.	Weight (Box)	Weight	Device (W x H x D)	Box
beige	4019588031951	1033/2195	2,8 kg	2 kg	33 x 35 cm	40,5 x 39,5 x 22 cm
slate grey	4019588331952	1333/2195	2,8 kg	2 kg	33 x 35 cm	40,5 x 39,5 x 22 cm
brick red	4019588431959	1433/2195	2,8 kg	2 kg	33 x 35 cm	40,5 x 39,5 x 22 cm
polar white	4019588731950	1733/2195	2,8 kg	2 kg	33 x 35 cm	40,5 x 39,5 x 22 cm
yellow with smiley	4019588531956	1533/2195	2,8 kg	2 kg	33 x 35 cm	40,5 x 39,5 x 22 cm

TOP FEATURES

- Only 33 cm small
- 1 participant
- 1 orbital position (for example Astra 19.2 ° East)
- Especially suitable for balcony installation / Ideal for the city
- Ideal for ground and wall mounting

LOCAL OSCILLATOR

- Low band: 9,74 GHz
- High band: 10,7 GHz
- Accuracy: ± 1 MHz
- Phase noise: -75 @10kHz
- Temperature drift: ± 2,5 MHz

FILTER-NAVIGATION

- Number participants: 1
- Features: with LNB
- Number satellites: 1
- Diameter: 33 cm

LNB CONTROL

- Vertical: 12 - 14,5 V
- Horizontal: 16 - 20 V
- Band switch: 22 kHz

GENERAL CHARACTERISTICS

Material: Aluminium

Material strength: 1 mm

Coating: Powder-coated on both sites

including Wall bracket: Yes

HANDLING/COMFORT

SAT-Finder: Yes

INPUT FREQUENCY RANGE

Low band: 10,7 ... 11,7 GHz

High band: 11,7 ... 12,75 GHz

NOISE FACTOR

Lower frequency range: 0,7 dB max.

Upper frequency range: 0,7 dB max.

Noise figure: typ. 0,9 dB

OUTPUT FREQUENCY RANGE

Low band: 950 - 1.950 MHz

High band: 1.100 - 2.150 MHz

POWER SUPPLY

LNB voltage supply: 2 ... 20 V

Power consumption: max. 150 mA

PREPARED FOR

Number of clients: 1

Number of orbit positions: 1

TECHNICAL DATA

Rated measurement: 0,33 m

F/D: 0,6

Offset angle: 30 °

Gain: 30 dBi @11,3 GHz

Feed reception: 40 mm

SCOPE OF DELIVERY

Satellite dish 33 cm, LNB, Wall bracket, Screws, Tool, Mounting instruction